SONANCE

VISUAL EXPERIENCE DATA SHEET

VX66R

TECHNICAL SPECIFICATIONS

VX66R

96014 - Pair SKU

1" (25mm) ceramic dome, Ferrofluid-cooled, **Tweeter**

acoustic back chamber

Woofer 6.5" (165mm) Kevlar/ Nomex cone, rubber

surround, pivoting

Dispersion Technology Sinusoidal textured waveguide

Speaker Pivot Coincident woofer and tweeter, +/-13° pivot

43Hz - 20kHz +/-3dB Frequency Response

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum; 140 watts maximum

Sensitivity (2.83V/1m) 90dB SPI


Mounting Technology Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps

Round Micro Trim Grille (Dia) 9.62" (244.4mm) Round Trimless Grille (Dia) 9.28" (235.6mm)


Square Micro Trim Grill (WxH) 9.62" x 9.62" (244.4mm x 244.4mm) Square Trimless Grille (WxH) 9.28" x 9.28" (235.6mm x 235.6mm)

Speaker Mounting Depth (D) 4.92" (125mm) Mounting Depth + Retrofit Encl. 5.75" (146.1mm) Cut-Out Dims (Dia) 8.25" (210mm) **Shipping Weight** 9 lbs. (4.1kg)

DIMENSIONAL DRAWINGS




Cut-Out Diameter **Front View**



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 6" ROUND ACCESSORIES

| VX6R-GRILLE-T 6" Micro Trim Round Grille / Pair | 93575 |
|--|-------|
| VX6R-GRILLE-NT | |
| 6" Trimless Round Grille / Pair VX6SQ-T | 93576 |
| 6" Micro Trim Square Adapter / Pair | 96030 |
| VX6SQ-T-5PR 6" Micro Trim Square Adapter / 5xPair | 96033 |
| VX6SQ-NT | |
| 6" Trimless Square Adapter / Pair VX6SQ-NT-5PR | 93586 |
| 6" Trimless Square Adapter / 5xPair | 93589 |
| VX6-ENCL-R 6" Round Enclosure / Pair | 96343 |
| FLEXBRK-6-R | |
| 6" Round Flex Bracket / 5x Pair | 92337 |

LIMITED LIFETIME WARRANTY