

TECHNICAL INFORMATION



V2 Slight
Variation



Ready Ship



Recommend offset
pattern $\leq 33\%$



DCOF: > 0.42



Frost Resistant




Water Absorption:
 $\leq 0.5\%$



Made in USA



COLORS

		
Ash AUS CTAS	Black AUS CTBL	Denim AUS CTDN
		
Gray AUS CTGR	Jade AUS CTJD	Pearl AUS CTPR
		
Sand AUS CTSN	Smoke AUS CTSM	White AUS CTWH

Performance Characteristics

Breaking Strength	≥ 350 lbf
Chemical Resistance	Resistant
DCOF	> 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	$\leq 0.5\%$
Certifications	HPD, EPD, Greenguard VOC Free
Country of Origin	USA
Shade Variation Code	V2

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.63" x 47.25"	9mm	Matte/Natural
12" x 24"	11.75" x 23.63"	9mm	Matte/Natural
3" x 12"	2.75" x 11.75"	9mm	Matte/Natural
12" x 12" Evo Mosaic	11.75" x 11.75"	9mm	Matte/Natural
2" x 2" Mosaic	11.75" x 11.75"	9mm	Matte/Natural
6" x 12" Cove Base	5.88" x 11.75"	8.5mm	Matte/Natural
3" x 24" Bullnose	2.88" x 23.63"	9mm	Matte/Natural

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards



Please see virginiatile.com for details