



Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 25/09/2023 Revision date: 13/09/2023 Supersedes version of: 18/11/2020 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Urethane Isolation
Product code : BDS001077BU

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Anti Corrosion Products

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11 - F +32(0)52/45.00.34
hse@crcind.com - www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11
Office hours: 9-17h CET

| Country | Organisation/Company | Address | Emergency number | Comment |
|---------|--|------------------------------|------------------|--|
| Belgium | Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid | Rue Bruyn 1 1120 Brussels | +32 70 245 245 | Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee) |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Specific target organ toxicity – Repeated exposure, Category 2 H373
Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Warning

Contains :

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); 1-methoxy-2-propanol; monopropylene glycol methyl ether

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe mist/vapours.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|---------|--|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | EC-No.: 919-857-5 REACH-no: 01-2119463258-33 | 50 – 75 | Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066 |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | EC-No.: 919-446-0 REACH-no: 01-2119458049-33 | 5 – 10 | Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|-------|---|
| 1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit | CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35 | 1 – 5 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | EC-No.: 918-481-9 EC Index-No.: 649-327-00-6 REACH-no: 01-2119457273-39 | 1 – 5 | Asp. Tox. 1, H304 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Seek medical attention if irritation develops. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. Seek medical attention if irritation develops. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Repeated exposure may cause skin dryness or cracking. |

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Hazardous decomposition products in case of fire | : During fire, gases hazardous to health may be formed. |
|--|---|

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Firefighting instructions | : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

| | |
|----------------------|---|
| Protective equipment | : Wear appropriate protective equipment and clothing during clean-up. |
| Emergency procedures | : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) | |
|--|---|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | 1-Methoxypropanol-2 |
| IOEL TWA | 375 mg/m ³ |
| IOEL TWA [ppm] | 100 ppm |
| IOEL STEL | 568 mg/m ³ |
| IOEL STEL [ppm] | 150 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Belgium - Occupational Exposure Limits | |
| Local name | 1-Méthoxy-2-propanol # 1-Methoxy-2-propanol |
| OEL TWA | 184 mg/m ³ |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) | |
|---|--|
| OEL TWA [ppm] | 50 ppm |
| OEL STEL | 369 mg/m ³ |
| OEL STEL [ppm] | 100 ppm |
| Remark | D: la mention "D" signifie que la r sorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette r sorption peut se faire tant par contact direct que par pr sence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht. |
| Regulatory reference | Koninklijk besluit/Arr t  royal 11/05/2021 |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | |
|--|--------------------------|
| DNEL/DMEL (Workers) | |
| Long-term - systemic effects, dermal | 208 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 871 mg/m ³ |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 125 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 185 mg/m ³ |
| Long-term - systemic effects, dermal | 125 mg/kg bodyweight/day |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | |
| DNEL/DMEL (Workers) | |
| Long-term - systemic effects, dermal | 44 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 330 mg/m ³ |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 26 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 71 mg/m ³ |
| Long-term - systemic effects, dermal | 26 mg/kg bodyweight/day |
| 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) | |
| DNEL/DMEL (Workers) | |
| Acute - systemic effects, inhalation | 553,5 mg/m ³ |
| Acute - local effects, inhalation | 553,5 mg/m ³ |
| Long-term - systemic effects, dermal | 183 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 369 mg/m ³ |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 33 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 43,9 mg/m ³ |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) | |
|---|----------------------------|
| Long-term - systemic effects, dermal | 78 mg/kg bodyweight/day |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 10 mg/l |
| PNEC aqua (marine water) | 1 mg/l |
| PNEC aqua (intermittent, freshwater) | 100 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 52,3 mg/kg dwt |
| PNEC sediment (marine water) | 5,2 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 4,59 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 100 mg/l |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 18,75 mg/kg bodyweight/day |

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|------------------------------------|
| Physical state | : Liquid |
| Colour | : colourless to yellow. |
| Appearance | : Viscous liquid. |
| Odour | : Solvent. |
| Odour threshold | : Not available |
| Melting point | : Not applicable |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flammability | : Non flammable. |
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : 34 °C (closed cup) |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : Not applicable |
| Viscosity, kinematic | : 40 mm ² /s at 40 °C |
| Viscosity, dynamic | : 62 – 110 mPa·s at 20 °C |
| Solubility | : insoluble in water. |
| Partition coefficient n-octanol/water (Log Kow) | : Not applicable |
| Vapour pressure | : Not available |
| Vapour pressure at 50°C | : Not available |
| Density | : 0,875 g/cm ³ at 20 °C |
| Relative density | : 0,875 at 20 °C |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 520 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|--------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 5000 mg/kg |

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|-----------------------|--------------|
| LD50 oral rat | 4016 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 Inhalation - Rat | > 25,8 mg/l |

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|-----------------------------------|-------------------------|
| LD50 dermal rabbit | ≥ 3160 mg/kg bodyweight |
| LC50 Inhalation - Rat (Dust/Mist) | > 5610 mg/l/4h |

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: Not applicable

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: Not applicable

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

| | |
|------------------------|---|
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |
|------------------------|---|

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|-------------------------------------|-------------------------|
| LOAEL (oral, rat, 90 days) | 2757 mg/kg bodyweight |
| NOAEL (oral, rat, 90 days) | 919 mg/kg bodyweight |
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight |

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Urethane Isolation

| | |
|----------------------|--------------------------------|
| Viscosity, kinematic | 40 mm ² /s at 40 °C |
|----------------------|--------------------------------|

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|----------------------|-------------------------|
| Viscosity, kinematic | 1,33 mm ² /s |
|----------------------|-------------------------|

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|----------------------|--------------------------|
| Viscosity, kinematic | 1,848 mm ² /s |
|----------------------|--------------------------|

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|----------------------|------------------------|
| Viscosity, kinematic | 1,8 mm ² /s |
|----------------------|------------------------|

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Not rapidly degradable

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|------------------------------------|-------------|
| LC50 - Fish [1] | > 1000 mg/l |
| EC50 - Crustacea [1] | > 1000 mg/l |
| EC50 - Other aquatic organisms [1] | > 1000 mg/l |
| EC50 72h - Algae [1] | > 1000 mg/l |

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|------------------------------------|--------------------|
| LC50 - Fish [1] | 6812 mg/l |
| LC50 - Fish [2] | 20800 mg/l |
| EC50 - Crustacea [1] | 21100 – 25900 mg/l |
| EC50 - Other aquatic organisms [1] | 2954 mg/l |
| ErC50 algae | > 1000 mg/l |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|------------------------------------|--|
| LC50 - Fish [1] | > 1000 mg/l |
| EC50 - Other aquatic organisms [1] | > 1000 mg/l Daphnia magna (Water flea) |

12.2. Persistence and degradability

Urethane Isolation

| | |
|-------------------------------|---|
| Persistence and degradability | Not established. No data is available on the degradability of this product. |
|-------------------------------|---|

12.3. Bioaccumulative potential

Urethane Isolation

| | |
|---|----------------|
| Partition coefficient n-octanol/water (Log Kow) | Not applicable |
|---|----------------|

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

| | |
|---|-------|
| Bioconcentration factor (BCF REACH) | < 100 |
| Partition coefficient n-octanol/water (Log Pow) | 0,37 |

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Urethane Isolation

| | |
|---------------------------|---|
| Results of PBT assessment | Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII |
|---------------------------|---|

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|-------------------------------------|---------|---------|---------|---------|
| 14.1. UN number or ID number | | | | |
| UN 1263 | UN 1263 | UN 1263 | UN 1263 | UN 1263 |

Urethane Isolation

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| ADR | IMDG | IATA | ADN | RID |
|---|---|---|---|---|
| 14.2. UN proper shipping name | | | | |
| PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | Paint related material | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL |
| Transport document description | | | | |
| UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E) | UN 1263 PAINT RELATED MATERIAL, 3, III | UN 1263 Paint related material, 3, III | UN 1263 PAINT RELATED MATERIAL, 3, III | UN 1263 PAINT RELATED MATERIAL, 3, III |
| 14.3. Transport hazard class(es) | | | | |
| 3 | 3 | 3 | 3 | 3 |
|  |  |  |  |  |
| 14.4. Packing group | | | | |
| III | III | III | III | III |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No | Dangerous for the environment: No | Dangerous for the environment: No |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

| | |
|---|---------------------------|
| Classification code (ADR) | : F1 |
| Special provisions (ADR) | : 163, 367, 650 |
| Limited quantities (ADR) | : 5I |
| Excepted quantities (ADR) | : E1 |
| Packing instructions (ADR) | : P001, IBC03, LP01, R001 |
| Special packing provisions (ADR) | : PP1 |
| Mixed packing provisions (ADR) | : MP19 |
| Portable tank and bulk container instructions (ADR) | : T2 |
| Portable tank and bulk container special provisions (ADR) | : TP1, TP29 |
| Tank code (ADR) | : LGBF |
| Vehicle for tank carriage | : FL |
| Transport category (ADR) | : 3 |
| Special provisions for carriage - Packages (ADR) | : V12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Hazard identification number (Kemler No.) | : 30 |
| Orange plates | : |



Tunnel restriction code (ADR) : D/E

Transport by sea

| | |
|-----------------------------------|----------------------|
| Special provisions (IMDG) | : 163, 223, 367, 955 |
| Limited quantities (IMDG) | : 5 L |
| Excepted quantities (IMDG) | : E1 |
| Packing instructions (IMDG) | : P001, LP01 |
| Special packing provisions (IMDG) | : PP1 |
| IBC packing instructions (IMDG) | : IBC03 |
| Tank instructions (IMDG) | : T2 |
| Tank special provisions (IMDG) | : TP1, TP29 |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| | |
|------------------------------------|--|
| EmS-No. (Fire) | : F-E |
| EmS-No. (Spillage) | : S-E |
| Stowage category (IMDG) | : A |
| Properties and observations (IMDG) | : Miscibility with water depends upon the composition. |

Air transport

| | |
|--|-----------------|
| PCA Excepted quantities (IATA) | : E1 |
| PCA Limited quantities (IATA) | : Y344 |
| PCA limited quantity max net quantity (IATA) | : 10L |
| PCA packing instructions (IATA) | : 355 |
| PCA max net quantity (IATA) | : 60L |
| CAO packing instructions (IATA) | : 366 |
| CAO max net quantity (IATA) | : 220L |
| Special provisions (IATA) | : A3, A72, A192 |
| ERG code (IATA) | : 3L |

Inland waterway transport

| | |
|-----------------------------------|-----------------|
| Classification code (ADN) | : F1 |
| Special provisions (ADN) | : 163, 367, 650 |
| Limited quantities (ADN) | : 5 L |
| Excepted quantities (ADN) | : E1 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01 |
| Number of blue cones/lights (ADN) | : 0 |

Rail transport

| | |
|---|---------------------------|
| Classification code (RID) | : F1 |
| Special provisions (RID) | : 163, 367, 650 |
| Limited quantities (RID) | : 5L |
| Excepted quantities (RID) | : E1 |
| Packing instructions (RID) | : P001, IBC03, LP01, R001 |
| Special packing provisions (RID) | : PP1 |
| Mixed packing provisions (RID) | : MP19 |
| Portable tank and bulk container instructions (RID) | : T2 |
| Portable tank and bulk container special provisions (RID) | : TP1, TP29 |
| Tank codes for RID tanks (RID) | : LGBF |
| Transport category (RID) | : 3 |
| Special provisions for carriage – Packages (RID) | : W12 |
| Colis express (express parcels) (RID) | : CE4 |
| Hazard identification number (RID) | : 30 |

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 520 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

| Abbreviations and acronyms: | |
|-----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |

Urethane Isolation

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Abbreviations and acronyms: | |
|-----------------------------|--|
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment – Chronic Hazard, Category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment – Chronic Hazard, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| STOT RE 1 | Specific target organ toxicity – Repeated exposure, Category 1 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.