

ASPEN GLAZED PORCELAIN

PACKAGING INFORMATION

DESCRIPTION	LBS/BOX	KGS/BOX	PCS/BOX	SQFT/BOX	M ² /BOX	BXS/SKD	SQFT/SKID	M ² /SKID
ASPEN								
8 x 48 in (19.7 x 120 cm) ASPEN RECTIFIED PORCELAIN TILE	49.72	22.55	4	10.23	0.95	45	460.35	42.75
6 x 36 in (14.7 x 90 cm) ASPEN PORCELAIN TILE	53.37	24.21	8	11.41	1.06	48	547.68	50.88
4 x 24 in (9.8 x 60 cm) ASPEN RECTIFIED PORCELAIN TILE	29.88	13.55	10	6.35	0.59	84	533.4	49.56
16 x 16 in (39.6 x 39.6 cm) ASPEN MARQUETRY PORCELAIN MOSAICS	62.21	28.22	8	13.45	1.25	36	484.2	45

TECHNICAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	8 x 48 in (19.7 x 120 cm)	6 x 36 in (14.7 x 90 cm)	4 x 24 in (9.8 x 60 cm)
			MATTE	MATTE	MATTE
THICKNESS		mm – in	10.3 mm	10 mm	10.3 mm
WATER ABSORPTION	ASTM C-373 / EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	ASTM C-1027 / EN ISO 10545-7	(PEI)	4	4	4
SCRATCH HARDNESS		(Mohs)	7	7	7
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 300	≥ 300	≥ 300
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A Resistant	Class A Resistant	Class A Resistant
STAIN RESISTANCE	EN ISO 10545-14		Class 5	Class 5	Class 5
FROST RESISTANCE	EN ISO 10545-12 / ASTM C1026		Pass	Pass	Pass
DCOF (WET)	ANSI B101.3		≥ 0.42	≥ 0.42	≥ 0.42
R VALUE			R9	R9	R9
SHADE VARIATION			V3	V3	V3