



Polarity and Conduction and Puncture Test	
Dielectric Voltage Withstand Test : 2000V / 1 Sec	
Electrical Performance (20°C)	
Item	Parameter
Conductor Resistance	≤ 13.3Ω/1000m
Voltage Rating	AC 300/500V

PINOUT			
SF-03		SF-300	WIRE
E		E	YE/GN
L		L	BROWN
N		N	BLUE

⑥	Mini Tie	Mini Tie Black	1PC
⑤	Molding	Molding 40P PVC Black	AR
④	Housing	SF-300 One piece of inner frame, IEC C19, Three plug, Black ABS	1PC
③	Terminal	IEC C19 Three plug Female Straight insert of Common terminal, brassy yellow, 1.5mm²	3PCS
②	Terminal	SF-03 One piece of Inner frame Three plug Black Nickel plated 1.5mm²	1PC
①	Cable	H05VV-F 1.5mm²x3C Black PVC	1PC
No.	TITLE	DESCRIPTION	Q'TY

THIRD ANGLE PROJECTION

GENERAL NOTES
DIMENSIONS ARE IN MM - DO NOT SCALE

THIS DOCUMENT CONTAINS CONFIDENTIAL, PROPRIETARY INFORMATION THAT IS PROPERTY OF STARTECH.COM

PRODUCT ID	PXTEUC192M
DESCRIPTION	2m (6ft) Computer Power Cord, 16AWG, EU Schuko to C19, 16A 250V
DO NOT SCALE	SHEET: 1 OF: 1
UPLOAD DATE: 10/25/2024	