WOLVERINE BRASS, INC.

PRO SERIES STAINLESS STEEL KITCHEN-LAVATORY CONNECTORS WITH 2 BRASS NUTS

CONSTRUCTION:
- ☐ CORROSION RESISTANT 304 STAINLESS STEEL BRAIDING.
- ☐ SUPERIOR STRENGTH AND FLEXIBILITY.
- ☐ 12 POINT STAINLESS CRIMPING.
- ☐ CHLORAMINE RESISTANT REINFORCED PVC TUBING.

OPERATION:
- ☐ TWO BRASS NUTS.
- ☐ 160 PSI MAX PRESSURE @ 33° - 140° F OPERATING TEMPERATURE.

STANDARDS:
- ☐ IAPMO/UPC CERTIFIED:
  - — ASME A112.18.6
  - — NSF/ANSI 61a
- ☐ LOW LEAD COMPLIANT (0.25% Pb MAX).

CATALOG #	DESCRIPTION	A
57634	3/8" OD x 1/2" FIP	6"
57635	3/8" OD x 1/2" FIP	9"
57572	3/8" OD x 1/2" FIP	12"
57573	3/8" OD x 1/2" FIP	16"
57574	3/8" OD x 1/2" FIP	20"
57575	3/8" OD x 1/2" FIP	24"
57660	3/8" OD x 1/2" FIP	36"
57672	1/2" OD x 1/2" FIP	12"
57673	1/2" OD x 1/2" FIP	16"
57674	1/2" OD x 1/2" FIP	20"
57676	3/8" FL x 1/2" FIP	12"
57677	3/8" FL x 1/2" FIP	16"
57678	3/8" FL x 1/2" FIP	20"
57576	1/2" FIP x 1/2" FIP	12"
57577	1/2" FIP x 1/2" FIP	16"
57578	1/2" FIP x 1/2" FIP	20"

