



1. General description

Protective coating with an exceptional brilliance, similar to freshly Hot Dip Galvanized parts. Keeps its brilliance in time.

2. Features

- Excellent touch-up for galvanised surfaces.
- No ozone depleting action.
- Totally free of lead and chromates.
- Preserves its shine and intensive colour for a long time.
- Protects metals and alloys.

3. Applications

- Touch-up of parts after hot dip galvanising.
- Standard cutting operations.

4. Directions

- Shake until the agitator ball moves freely in the can.
- Repeat frequently during the application.
- Use only with adequate ventilation.
- Spray from a distance of approximately 20 - 30 cm.
- Allow to dry completely before reactivation.
- To remove residues or excess product, use one of the CRC cleaners.
- Clean the aerosol valve by turning the can upside down and spraying until only propellant escapes.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

| | |
|-------------------------|-----------------------------------|
| Appearance | Liquid. |
| Color | Grey. |
| Density | 0.905 g/cm ³ (@ 20°C). |
| Flash Point | < 0 °C |
| Application temperature | min 5 °C |



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





| | |
|--------------------------------------|------------------------|
| Horizontal spread active product | >1 m ² /can |
| Drying time active product | to touch < 5 min |
| salt spray resistance active product | 100 h |

6. Packaging

| | | |
|---------|-----------|--------------|
| Aerosol | 12x400 ML | Ref. : 30713 |
|---------|-----------|--------------|

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-GALVA_BRILLO-20140418

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

