



THREAD DETAIL INFORMATION
5 THREADS PER INCH, 0.200 PITCH
450° (1 1/4 TURNS) FULL DEPTH THREAD

REFERENCE	TOLERANCE	DIMENSION	UNITS
T	±0.017 [0.43]	3.485 [88.52]	in [mm]
E	±0.017 [0.43]	3.375 [85.73]	in [mm]
I	±0.015 [0.38]	3.234 [82.14]	in [mm]
S'	±0.015 [0.38]	0.140 [3.56]	in [mm]
H	±0.010 [0.25]	0.517 [13.13]	in [mm]
OAH	±0.015 [0.38]	3.165 [80.39]	in [mm]
MAXIMUM OD	±0.017 [0.43]	3.500 [88.90]	in [mm]
PART WEIGHT	±3.00	38.00	g
MAXIMUM VOLUME	±5%	14.03 [415]	oz [cc]

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: