MWUH SERIES
HORIZONTAL/DOWNFLOW UNIT HEATER

IDEAL SPACES
- Factories
- Garages
- Maintenance Rooms
- Warehouses
- Public Buildings
- Service Stations
- Workshops
- Stairwells

COLORS
- Neutral Gray

DIMENSIONS
- 14"L x 12-1/2"H x 11-1/4"D

TEMP RANGE
- 45°– 90°F

CFM
- 270

- Heater comes equipped with ceiling-mount bracket for horizontal or vertical flow mounting or any position in between
- Built-in single-pole thermostat
- Copper-brazed steel fins with steel sheathed tubular elements for uniform heating and longevity
- Adjustable louvers control air throw direction
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- High limit cut-off with visual alarm automatically shuts off current in event of overheating and reactivates unit when temperature returns to normal
- Disconnect switch (DS30) option available for heaters 24 amps or lower.

c UL us

5 YEAR WARRANTY ELEMENT

1 YEAR WARRANTY WORKMANSHIP

MWUH SERIES
HORIZONTAL/DOWNFLOW UNIT HEATER

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	VOLTS	WATTS	BTU/HR	FAN MOTOR WATTS	CONTROL & FAN MOTOR VOLTS	FAN MOTOR RPM	AIR THROW (FT.)	MIN. MOUNTING HEIGHT (FT.)	HEATER AMPS	MIN. CKR. AMPS	SHIP WT. (LBS.)
MWUH5004	6 85360 03880 3	208	1874	6396	6	208	1350	16	6	9.0	11.3	24
			2500	8553						12.0	15.0	
			2812	10659						15.0	18.5	
			3750	12799						18.0	22.5	
		240	2500	8533		240				10.4	13.0	
			3332	11365						13.9	17.4	
			3750	14215						17.4	21.8	
			5000	17065						20.9	26.1	
MWUH7504	6 85360 14870 0	208	2812	9598	6	208	1400	18	8	13.5	11.3	27
			3750	12799						18.0	15.0	
			4685	15990						22.5	18.5	
			5625	19198						27.1	22.5	
		240	3750	12799		240				15.6	19.5	
			5000	17065						20.8	26.0	
			6250	21331						26.0	32.5	
			7500	25598						31.3	39.1	
MWUH5008	6 85360 04771 3	208	2500	8533	6	208	1400	16	8	12.0	–	26
			3332	11365						16.0	15.0	
			4165	14215						20.0	20.0	
			5000	17065						24.0	26.0	

NOTE: Disconnect switch (DS30) option available for heaters 24 amps or lower. Optional CWB1A combination wall/ceiling bracket available.