CL3R, Shielded Stranded 12 AWG & 14 AWG, 300V

CL3R - Shielded Conductors
14 AWG & 12 AWG
PVC/PVC

Security and Alarm Cable



Category Conductor Description:

- Stranded bare copper to ASTM B-3, B-8, and B-286

Category Insulation Description:

- Color coded Semi-Regid Polyvinyl Chloride (SR-PVC)

Shield:

- Overall polyester supported aluminum foil Stranded tinned copper drain wire

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) Includes ripcord

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725 Type CL3R
- CSA CMG 60C FT-4

PART NUMBER TABLE							
Part#	**Gauge**	**Conductors**	**Insulation Thickness**	**Jacket Thickness**	**Outside Diameter Inches**	**Material Weight (Lbs./M')**	**Material Weight (KG/KM)**
DS11402	14	2	0.013	0.015	0.245	40.3	59
DS11403	14	3	0.013	0.015	0.234	54.3	80
DS21404	14	4	0.013	0.015	0.257	70	104
DS11202	12	2	0.013	0.015	0.281	60	89

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 ™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC