



Color :  White

UPC Code : 078477434314

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



T5280-W

15 Amp, 125 Volt, Decora Plus Surge Protective Duplex Receptacle Outlet, Commercial Grade

Decora Plus Surge Protective Duplex Receptacle Outlet, Commercial Specification Grade, Tamper-Resistant, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Technical Information

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Polycarbonate

Clamp Nuts : Zinc-Plated Steel

Face Material : Nylon

Ground Clips : Brass-Plated
Steel

Grounding Screw : Brass-
Plated Steel

Line Contacts : Brass Triple-
Wipe

Shutter Mechanism : Delrin®
Acetal

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Back or Side
Wire

Torque Range : 14-16 inch
pounds

Yoke : Zinc-Plated Steel

Product Features

Brand : Decora Plus

Color : White

Device Type : Duplex
Receptacle Outlet

Feature : Tamper-Resistant

Function : Surge Protective

Grade : Commercial
Specification Grade

NEMA : 5-15R

VPR : L-N: 600V, L-G: 700V, N-G: 600V


Warranty

Warranty : 5-Year Limited

NEMA : WD-6

NOM : 057

Dimensional Drawing



Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.