

6.5W (50W Replacement) Warm White (2700K) MR16 GU10 Dimmable LED Enhance Mini Reflector Light Bulb (6-Pack)

Product Specifications

Item Number: **BPGU10/500/6UK**



- Highest quality energy efficient LED light
- Dependable reflector for security or track lighting
- Long life bulbs are rated to provide up to 30,000 hours of reliable light

Lighting technology used	LED
Non-directional or directional	Non-Directional
Light source cap-type (or other electric interface)	GU10
Correction factor C depending on light source characteristics-Main or non-mains	Non-Main
Connected light source (CLS):	
Useful luminous flux(Lm)*	500
Correlated colour temperature (K) *	2700
Chromaticity coordinate (x):	
Chromaticity coordinate (y):	
The beam angle or range of beam angles(0)*	38
Beam angle correspondence : Sphere or wide cone or narrow cone	
Electrical interface details*	220-240VAC, 50/60 Hz
The L70B50 life time expressed in hours	30,000
The on-mode power (Pon) expressed in W	6.5
Lamp Dimensions(mm)	53.5*50
The standby power (Psb) expressed in W	N/A
The networked standby power (Pnet) for CLS expressed in W	N/A
The Colour rendering index 80	82.6
Survival factor (Max value =1)	1
Lumen maintenance factor (Max value =1)	98.11%
Displacement factor (Max value =1)	0.761
Colour consistency in McAdam ellipses (Max value =9)	5.3
Flicker metric (Max value =9.9)	0.098
Stroboscopic effect metric (Max value =9.9)	0.603
Spectral power distribution in the range 250 nm to 800 nm, at full-load (File to be uploaded)	
If the light source is designed for optimum use in nonstandard conditions (such as ambient temperature Ta \neq 25 0C or specific thermal management is necessary)	N/A
A warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods	Dimmable
Mercury content x,x mg (if applition) 0,0	0
Energy consumption in on-mode (KWh/1000h):	
Energy Efficacy Class	F