

VISUAL COMFORT & Co.

6522701-112: Small One Light Pendant



Collection: Hanalei

Supplied with pre-laced, adjustable 14-feet of wire and 12-feet of chain for a customized look

Mounting hardware included for use on flat, slope, vaulted or cathedral ceilings

Install a dimmer switch for a warm glow effect and easily change the look and feel of the room

Designed for damp and dry environments allowing for occasional water moisture, such as bathrooms, covered patios or porches

1-Year manufacturer warranty

UPC #:785652095061

Finish: Midnight Black (112)

Dimensions:

Diameter: 11.5"
Height: 13.25"
Weight: 5.1 lbs.

Wire: 120" (color;Black)

Chain: 72"

Mounting Proc.: Screw Collar - Chain

Connection: Mounted To Box

Bulbs:

1 - Medium A19 75.0w Max. 120v Not included

Features:

- Easily converts to LED with optional replacement lamps
- Meets Title 24 energy efficiency standards
- Title 24 compliant if used with Joint Appendix (JA8) approved light bulbs listed in the California Energy Commission Appliance database.
- Supplied with wire pre-laced through chain

Material List:

1 Body - Steel - Midnight Black

Safety Listing:

Safety Listed for Damp Locations

Instruction Sheets:

English (6522701 6622701 6722701)

Trilingual (English, Spanish, and French) (6522701 6622701 6722701)

Backplate / Canopy Details:

| Type | Height / Length | Width | Depth | Diameter | Outlet Box Up | Outlet Box Down |
|--------|-----------------|-------|-------|----------|---------------|-----------------|
| Canopy | 1.0 | | | 5.5 | | |

Shipping Information:

| Package Type | Product # | Quantity | UPC | Length | Width | Height | Cube | Weight | Fr. Class | UPS Ship |
|--------------|-------------|----------|----------------|--------|-------|--------|-------|--------|-----------|----------|
| Individual | 6522701-112 | 1 | 785652095061 | 14.4 | 14.4 | 15.9 | 1.91 | 8.0 | 0 | Yes |
| Master Pack | 6522701-112 | 0 | 10785652095068 | | | | | | | No |
| NJ Pallet | | 45 | | 48.0 | 40.0 | 77.0 | 85.56 | 360.0 | | No |
| NV Pallet | | 45 | | 48.0 | 40.0 | 77.0 | 85.56 | 360.0 | | No |