

SONANCE

POWERPIPE X SERIES DATA SHEET

PPX15

TECHNICAL SPECIFICATIONS

SKU	93788 - Each
Woofer	15" (381mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	29Hz - 90Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	94dB SPL
Enclosure	MDF (Medium Density Fiberboard)
Finish	Textured Black
Recommended Power	600 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502 3004 6008 Sonance DSP 2-750 MKIII
Tube Inside Diameter	5.98" (152mm)
Tube Length	25.59" (650mm)
Product Dims w/ Feet (WxHxD)	17.72" x 18.33" x 16.93" (450mm x 466mm x 430mm)
Product Dims w/o Feet (WxHxD)	17.72" x 17.72" x 16.93" (450mm x 450mm x 430mm)
Product Weight	68.26 lbs. (30.96kg)
Shipping Weight	79.37 lbs. (36kg) Team lift required

ACCESSORIES

PPX-8R | 93796
PPX 8" XPC Grille Connector

PPX-6R | 93795
PPX 6" XPC Grille Connector

PPX-6-90 | 93793
PPX 90-Degree Adapter

PPX-3.5x16-2-STR | 93790
PPX Straight Toekick Connector and Grille

PPX-3.5x16-2-90 | 93789
PPX 90-Degree Toekick Connector and Grille

PPX TOEKICK REPLACEMENT GRILLE | 93799
Straight or 90-Degree Toekick Connector Required

DIMENSIONAL DRAWINGS

