



TECHNICAL INFORMATION



Ready Ship



Recommend offset pattern $\leq 33\%$



DCOF: ≥ 0.42



Frost Resistant



Water Absorption: $\leq 0.4\%$



Made in USA



COLORS



Black
MLS ARBL



Clay
MLS ARCL



Steel
MLS ARST



White
MLS ARWH

Performance Characteristics

Breaking Strength	≥ 300 lbf
Chemical Resistance	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	$\leq 0.4\%$
Certifications	N/A
Country of Origin	USA
Shade Variation Code	N/A

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 24"	24" x 24"	8mm	Matte/Natural
12" x 24"	12" x 24"	8mm	Matte/Natural
2" x 2" Mosaic	12" x 12"	8mm	Matte/Natural

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

