



Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 21/01/2025 Revision date: 28/08/2024 Supersedes version of: 29/05/2024 Version: 5.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Striping Paint
UFI : AHCY-E849-Q004-0ETV
Product code : BDS001274AE
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Paints

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11, F +32(0)52/45.00.34
hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11
Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness.

Striping Paint


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)	: Danger
Contains	: Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics;n-butyl acetate;ethyl acetate
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P280 - Wear protective gloves/eye protection. P312 - Call a POISON CENTRE or doctor if you feel unwell. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains Fatty acids, C18-unsatd, dimers, compds. with coco alkylamines (68647-95-0), Cobalt bis(2-ethylhexanoate) (136-52-7). May produce an allergic reaction.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 927-241-2 REACH-no: 01-2119471843-32	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 EUH066

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
ethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] substance with national workplace exposure limit(s) (BE) (Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	5 – 10	Carc. 2, H351
Talc (Mg ₃ H ₂ (SiO ₃) ₄) substance with national workplace exposure limit(s) (BE)	CAS-No.: 14807-96-6 EC-No.: 238-877-9 REACH-no: 01-2120140278-58	5 – 10	Not classified
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC-No.: 245-018-1 REACH-no: 01-2119979088-21	< 0,3	Repr. 1B, H360D
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines	CAS-No.: 68647-95-0 EC-No.: 614-682-8 REACH-no: 01-21120099181-55	< 0,25	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC-No.: 205-250-6 REACH-no: 01-2119524678-29	< 0,1	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 1A, H360F Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.
--------------------	---

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

dimethyl ether (115-10-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Dimethylether
IOEL TWA	1920 mg/m ³ 1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Belgium - Occupational Exposure Limits

Local name	Oxyde de diméthyle # Dimethylether
OEL TWA	1920 mg/m ³ 1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

n-butyl acetate (123-86-4)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³ 50 ppm
IOEL STEL	723 mg/m ³ 150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

Belgium - Occupational Exposure Limits

Local name	Acétate de n-butyle # n-Butylacetaat
OEL TWA	238 mg/m ³

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
	50 ppm
OEL STEL	712 mg/m ³
	150 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOEL TWA	734 mg/m ³
	200 ppm
IOEL STEL	1468 mg/m ³
	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Belgium - Occupational Exposure Limits	
Local name	Acétate d'éthyle # Ethylacetaat
OEL TWA	734 mg/m ³
	200 ppm
OEL STEL	1468 mg/m ³
	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Belgium - Occupational Exposure Limits	
Local name	Titane (dioxyde de) # Titaandioxide
OEL TWA	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Talc (Mg3H2(SiO3)4) (14807-96-6)	
Belgium - Occupational Exposure Limits	
Local name	Talc (sans fibre d'amiante, poussières alvéolaires) # Talk (asbestvrij, inadembaar stof)
OEL TWA	2 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
DNEL and PNEC	
dimethyl ether (115-10-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	1894 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	471 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,155 mg/l
PNEC aqua (marine water)	0,016 mg/l

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dimethyl ether (115-10-6)	
PNEC aqua (intermittent, freshwater)	1549 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,681 mg/kg dwt
PNEC sediment (marine water)	0,069 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,045 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	160 mg/l
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	77 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	871 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	46 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	185 mg/m ³
Long-term - systemic effects, dermal	46 mg/kg bodyweight/day
n-butyl acetate (123-86-4)	
PNEC (Water)	
PNEC aqua (freshwater)	0,18 mg/l
PNEC aqua (marine water)	0,018 mg/l
PNEC aqua (intermittent, freshwater)	0,36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,981 mg/kg dwt
PNEC sediment (marine water)	0,0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35,6 mg/l
ethyl acetate (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m ³
Acute - local effects, inhalation	1468 mg/m ³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m ³
Long-term - local effects, inhalation	734 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m ³
Acute - local effects, inhalation	734 mg/m ³

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)	
Long-term - systemic effects, oral	4,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m ³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,24 mg/l
PNEC aqua (marine water)	0,024 mg/l
PNEC aqua (intermittent, freshwater)	1,65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,15 mg/kg dwt
PNEC sediment (marine water)	0,115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l
Talc (Mg3H2(SiO3)4) (14807-96-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	2,16 mg/m ³
Acute - local effects, inhalation	3,6 mg/m ³
Long-term - systemic effects, dermal	43,2 mg/kg bodyweight/day
Long-term - local effects, dermal	4,54 mg/cm ²
Long-term - systemic effects, inhalation	2,16 mg/m ³
Long-term - local effects, inhalation	3,6 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1,08 mg/m ³
Acute - systemic effects, oral	160 mg/kg bodyweight/day
Acute - local effects, inhalation	1,8 mg/m ³
Long-term - systemic effects, oral	160 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,08 mg/m ³
Long-term - systemic effects, dermal	21,6 mg/kg bodyweight/day
Long-term - local effects, dermal	2,27 mg/cm ²
Long-term - local effects, inhalation	1,8 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	597,97 mg/l
PNEC aqua (marine water)	141,26 mg/l
PNEC aqua (intermittent, freshwater)	597,97 mg/l
PNEC aqua (intermittent, marine water)	141,26 mg/l

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Talc (Mg₃H₂(SiO₃)₄) (14807-96-6)	
PNEC (Sediment)	
PNEC sediment (freshwater)	31,33 mg/kg dwt
PNEC sediment (marine water)	3,13 mg/kg dwt
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
PNEC (Water)	
PNEC aqua (freshwater)	0,36 mg/l
PNEC aqua (marine water)	0,036 mg/l
PNEC aqua (intermittent, freshwater)	0,493 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	6,37 mg/kg dwt
PNEC sediment (marine water)	0,637 mg/kg dwt
PNEC (Soil)	
PNEC soil	1,06 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	71,7 mg/l
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines (68647-95-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,51 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,91 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,13 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,45 mg/m ³
Long-term - systemic effects, dermal	0,25 mg/kg bodyweight/day
Long-term - local effects, dermal	86,5 µg/cm ²
PNEC (Water)	
PNEC aqua (freshwater)	0,000393 mg/l
PNEC aqua (marine water)	0,0000393 mg/l
PNEC aqua (intermittent, freshwater)	0,00393 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,0395 mg/kg dwt
PNEC sediment (marine water)	0,00395 mg/kg dwt
PNEC (Soil)	
PNEC soil	2 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,416 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	180 mg/l

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cobalt bis(2-ethylhexanoate) (136-52-7)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	235,1 µg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	175 µg/kg bodyweight/day
Long-term - local effects, inhalation	37 µg/m³
PNEC (Water)	
PNEC aqua (freshwater)	1,06 µg/l
PNEC aqua (marine water)	2,36 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	53,8 mg/kg dwt
PNEC sediment (marine water)	69,8 mg/kg dwt
PNEC (Soil)	
PNEC soil	10,9 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0,37 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Vinyl polyalcohol protective gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Full face piece respirator (organic vapours). Filter type: A - P2

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: DME propelled liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 11 °C
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -37 °C (closed cup)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: < 7 mm ² /s at 40 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: < 110 kPa at 20 °C
Vapour pressure at 50°C	: Not available
Density	: 0,918 g/cm ³ at 20 °C
Relative density	: 0,92 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 25 – 50 %

Other safety characteristics

VOC content : 603 g/l (Cat.II B(e) VOC max 840 g/L)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

dimethyl ether (115-10-6)

LC50 Inhalation - Rat 308,5 mg/l/4h

LC50 Inhalation - Rat [ppm] 164000 ppm

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LD50 oral rat > 15000 mg/kg bodyweight

LD50 dermal rabbit ≥ 3160 mg/kg bodyweight

LC50 Inhalation - Rat ≥ 6,1 mg/l/4h

n-butyl acetate (123-86-4)

LD50 oral rat 10760 mg/kg

LD50 dermal rabbit > 17600 mg/kg

LC50 Inhalation - Rat (Dust/Mist) 23,4 mg/l/4h

ethyl acetate (141-78-6)

LD50 oral 4934 mg/kg bodyweight

LD50 dermal rabbit > 20000 mg/kg bodyweight

Talc (Mg₃H₂(SiO₃)₄) (14807-96-6)

LD50 oral rat > 5000 mg/kg bodyweight

LD50 dermal rat > 2000 mg/kg bodyweight

2-ethylhexanoic acid, zirconium salt (22464-99-9)

LD50 oral rat > 5000 mg/kg bodyweight

LD50 dermal rat > 2000 mg/kg bodyweight

Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines (68647-95-0)

LD50 oral rat > 2000 mg/kg bodyweight

LD50 dermal rat > 5000 mg/kg bodyweight

Cobalt bis(2-ethylhexanoate) (136-52-7)

LD50 oral rat 3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000

LD50 dermal rat > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

LC50 Inhalation - Rat > 2000 mg/kg

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: Not applicable

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
pH	6,2
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
n-butyl acetate (123-86-4)	
pH	6,2
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight
NOAEC (inhalation, rat, vapour, 90 days)	> 10,4 mg/l air
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight
2-ethylhexanoic acid, zirconium salt (22464-99-9)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines (68647-95-0)	
NOAEL (oral, rat, 90 days)	12,5 mg/kg bodyweight
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met).
Striping Paint	
Vaporizer	Aerosol
Viscosity, kinematic	< 7 mm ² /s at 40 °C
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Viscosity, kinematic	1,06 mm ² /s

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)

Viscosity, kinematic	0,83 mm ² /s
----------------------	-------------------------

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met).

dimethyl ether (115-10-6)

LC50 - Fish [1]	> 4,1 g/l
EC50 - Crustacea [1]	> 4,4 g/l Daphnia magna (Water flea)
EC50 96h - Algae [1]	154917 mg/l

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LC50 - Fish [1]	10 – 30 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	22 – 46 mg/l Daphnia magna (Water flea)

n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674,7 mg/l
LOEC (chronic)	47,6 mg/l
NOEC (chronic)	23,2 mg/l
NOEC chronic algae	200 mg/l

ethyl acetate (141-78-6)

LC50 - Fish [1]	230 mg/l
EC50 - Other aquatic organisms [1]	717 mg/l Daphnia magna (Water flea)
NOEC (chronic)	2,4 mg/l 21 d

Talc (Mg₃H₂(SiO₃)₄) (14807-96-6)

LC50 - Fish [1]	89581,02 mg/l
LC50 - Fish [2]	110000 mg/l
EC50 96h - Algae [1]	7202,7 mg/l
NOEC (chronic)	1459,798 mg/l 30 d

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexanoic acid, zirconium salt (22464-99-9)

LC50 - Fish [1]	> 100 mg/l <i>Oryzias latipes</i>
LOEC (chronic)	63 mg/l <i>Daphnia magna</i> (21 d)

Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines (68647-95-0)

LC50 - Fish [1]	55 mg/l <i>Danio rerio</i>
EC50 - Crustacea [1]	34,5 mg/l <i>Daphnia magna</i>
EC50 72h - Algae [1]	0,393 mg/l <i>Desmodesmus subspicatus</i>
NOEC (chronic)	0,013 mg/l <i>Daphnia magna</i> (21 d)

Cobalt bis(2-ethylhexanoate) (136-52-7)

LC50 - Fish [1]	1,512 mg/l
EC50 - Crustacea [1]	5,89 mg/l <i>Daphnia magna</i>
EC50 72h - Algae [1]	0,654 mg/l

12.2. Persistence and degradability

Striping Paint

Persistence and degradability	Not established. No data is available on the degradability of this product.
-------------------------------	---

12.3. Bioaccumulative potential

Striping Paint

Partition coefficient n-octanol/water (Log Kow)	Not applicable
---	----------------

dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0,07
---	------

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition coefficient n-octanol/water (Log Pow)	4
---	---

n-butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Pow)	2,3
---	-----

ethyl acetate (141-78-6)

Partition coefficient n-octanol/water (Log Pow)	0,7
---	-----

Cobalt bis(2-ethylhexanoate) (136-52-7)

Partition coefficient n-octanol/water (Log Pow)	2,96
---	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Striping Paint

Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII
---------------------------	--

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Striping Paint

Other information

No other effects known

Global warming potential (GWP)

0.50 (Fluorinated greenhouse gases - (EC) No 2024/573)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods


: Dispose of contents/container in accordance with licensed collector's sorting instructions.

European List of Waste (LoW, EC 2000/532)

: According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 603 g/l (Cat.II B(e) VOC max 840 g/L)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

Striping Paint

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Repr. 1A	Reproductive toxicity, Category 1A
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Fatty acids, C18-unsatd, dimers, compds. with coco alkylamines (68647-95-0), Cobalt bis(2-ethylhexanoate) (136-52-7). May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.