



PDU30BVHVT38F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 38-outlet (38 Front) OU vertical rack mount basic power distribution unit (PDU30BVHVT38F) provides 200/230V 30A output. It distributes power to 38 IEC-320 (8-C19 and 30-C13) receptacles from a single NEMA L6-30P twist lock plug, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

PDU30BVHVT38F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

Type Single Phase Single Single Single Single Straight, Twist Lock Single Sing	GENERAL		
INPUT Voltage 200V / 230V Frequency 50Hz/60Hz Maximum Input Current 30A (Derated to 24A) Plug Type NEMA L6-30P Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) 10.92 ENVIRONMENTAL		Basic PDU	
Voltage 200V / 230V Frequency 50Hz/60Hz Maximum Input Current 30A (Derated to 24A) Plug Type NEMA L6-30P Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) 10.92 ENVIRONMENTAL	Phase	Single Phase	
Frequency 50Hz/60Hz Maximum Input Current 30A (Derated to 24A) Plug Type NEMA L6-30P Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) 10.92 ENVIRONMENTAL	INPUT		
Maximum Input Current Plug Type NEMA L6-30P Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) To x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	Voltage	200V / 230V	
Plug Type NEMA L6-30P Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) ENVIRONMENTAL	Frequency	50Hz/60Hz	
Plug Style Straight, Twist Lock Cord Length 10' OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) 10.92 ENVIRONMENTAL	Maximum Input Current	30A (Derated to 24A)	
Cord Length OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (Ibs.) ENVIRONMENTAL	Plug Type	NEMA L6-30P	
OUTPUT Nominal Output Voltage 200V/230V Outlets - Total 38 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Plug Style	Straight, Twist Lock	
Nominal Output Voltage 200V/230V Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Cord Length	10'	
Outlets - Total 38 Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	ОИТРИТ		
Outlet Type IEC-320 C19/C13 Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x 1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Nominal Output Voltage	200V/230V	
Outlets - Front 8(C19)+30(C13) Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Outlets - Total	38	
Outlets - Rear 0 Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Outlet Type	IEC-320 C19/C13	
Overload Protection 16A x 2 PHYSICAL Rack Size 0U Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Yes Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Outlets - Front	8(C19)+30(C13)	
PHYSICAL Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	Outlets - Rear	0	
Rack Size OU Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers Yes External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	Overload Protection	16A x 2	
Form Factors Supported Vertical Rackmount, Wallmount Cord Retention Organizers External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	PHYSICAL		
Cord Retention Organizers External Site Ground Pin Yes Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	Rack Size	OU	
External Site Ground Pin Adjustable Mounting Brackets Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) ENVIRONMENTAL	Form Factors Supported	Vertical Rackmount, Wallmount	
Adjustable Mounting Brackets 3 sets (L-short, L-long, Flat) Dimensions (WxHxD) (in.) 70 x 1.75 x1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	Cord Retention Organizers	Yes	
Dimensions (WxHxD) (in.) 70 x 1.75 x 1.5 Weight (lbs.) 10.92 ENVIRONMENTAL	External Site Ground Pin	Yes	
Weight (lbs.) 10.92 ENVIRONMENTAL	Adjustable Mounting Brackets	3 sets (L-short, L-long, Flat)	
ENVIRONMENTAL	Dimensions (WxHxD) (in.)	70 x 1.75 x1.5	
	Weight (lbs.)	10.92	
Operating Temperature 32°E to 95°E / 0°C to 35°C	ENVIRONMENTAL		
32 1 t0 33 1 / 0 C t0 33 C	Operating Temperature	32°F to 95°F / 0°C to 35°C	
Operating Relative Humidity 0% - 95% non-condensing	Operating Relative Humidity	0% - 95% non-condensing	
Storage Temperature 5°F to 113°F / -15°C to 45°C	Storage Temperature	5°F to 113°F / -15°C to 45°C	
Maximum Operating Elevation 10,000 ft / 3,000 m	Maximum Operating Elevation	10,000 ft / 3,000 m	
Maximum Storage Elevation 50,000 ft / 15,000 m	Maximum Storage Elevation	50,000 ft / 15,000 m	
CERTIFICATIONS			
Safety UL60950_1 certified by ETL (USA), CSA C22.2 (Canada)	Safety		
Environmental RoHS Compliant	Environmental	RoHS Compliant	
WARRANTY	WARRANTY		
Product Warranty Lifetime	Product Warranty	Lifetime	