TPE FK

TPE Frame Kit

Product Description

NICOR's field install Frame kit allows for our recessed TPE Edgelit LED Troffers to be installed into drywall ceilings. Includes adapter frame and screws. The Frame kit is available for $2' \times 2'$, $2' \times 4'$ and $1' \times 4'$ troffers.

Construction

- Extruded aluminum frame with mitered corners
- Holes for support wires and additional mounting holes (0.25" DIA)

Mounting and installation

- Mounting holes for seismic wire
- Certified for direct contact with insulation

Finish

• Matte white powder coat finish

Warranty

• 1-year limited system warranty standard

Ceiling Opening Dimensions						
Series	(W) Width	(L) Length				
TPE10FK14	12 3/4" (324 mm)	48 3/4" (1238 mm)				
TPE10FK22	24 3/4" (629 mm) 24 3/4" (629 mm					
TPE10FK24	24 3/4" (629 mm)	48 3/4" (1238 mm)				

Trim Dimensions				
Series	(W) Width	(L) Length		
TPE10FK14	13 3/8" (340 mm)	49 3/8" (1254 mm)		
TPE10FK22	TPE10FK22 25 3/8" (645 mm) 25 3/8" (645 mm)			
TPE10FK24	25 3/8" (645 mm)	49 3/8" (1254 mm)		

Project					
Catalog					
Туре					
Date					
			,		
_	Trin	n Width (W	')———	i	
	••••	ii maai (m	,	_	_
			$\overline{}$]	
				Trimle	l ngth (L)
				111111 LC	
L					L
1	├── Ceil	ing Openir	ng———		



Ordering Information			
Series	Description		
TPE10FK14	1'x 4' Frame kit		
TPE10FK22	2'x2' Frame Kit		
TPE10FK24	2'x4' Frame Kit		

