

FLOOR

TIMBERBROOK™  
GLAZED PORCELAIN



Photo features Timberbrook Reclaimed Wood 8 x40 on the floor and Visual Impressions™ Beige 8 x 24 Quadrangle on the wall.

# TIMBERBROOK™ GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

Timberbrook™ by American Olean® captivates with the appeal of reclaimed barnwood that's been given new life in a durable porcelain tile. A naturally distressed wood look is captured perfectly with richly-blended colors on a unique plank size. The result is rustic elegance for a modern farmhouse design. Revive the personality of your room with this on-trend style that will last a lifetime.

TIMBERBROOK™

## GLAZED PORCELAIN FLOOR TILE



RECLAIMED WOOD TB15



PATINA GRAY TB18



FARMHOUSE TB16



BARN LOFT TB17




All or select items within this series meet the requirements for these qualifications. For more information visit [americanolean.com](http://americanolean.com).

AMERICANOLEAN.COM



SIZES

|   |                      |  | THICKNESS | SQ. FT./<br>CARTON | PIECES/<br>CARTON |
|---|----------------------|--|-----------|--------------------|-------------------|
|  | 8 x 40<br>Floor Tile | 7-7/8" x 39-3/8"<br>(20.00 cm x 100.00 cm) | 5/16"     | 10.75              | 5                 |

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

RELATIVE PRICING: Medium

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

|                     | ASTM# | FLOOR<br>RESULT |
|---------------------|-------|-----------------|
| Water Absorption    | C373  | < 0.5%          |
| Breaking Strength   | C648  | > 275 lbs.      |
| Scratch Hardness    | MOHS  | 8.0             |
| Chemical Resistance | C650  | Resistant       |
| Abrasion Resistance | C1027 | 3               |

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

USAGE

| FLOORS | WALLS | COUNTERTOPS |
|--------|-------|-------------|
| F      | W     | C           |

APPLICATIONS

|  | TARGET<br>DCOF WET | SUITABLE |
|--|--------------------|----------|
| Dry & Level – Interior Floor   | N/A                | ●        |
| Wet & Level – Interior Floor   | ≥ 0.42             | ●        |
| Shower Floors<br>(Residential or Light Commercial)   | ≥ 0.42             |          |
| Exterior Floor Applications<br>(including pool decking & other<br>wet areas with minimal footwear) | ≥ 0.60             |          |
| Ramps & Inclines   | ≥ 0.65             |          |
| Walls/Backsplashes   | N/A                | ●        |
| Countertops  | N/A                | ●        |
| Pool Linings   | N/A                |          |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [americanolean.com](http://americanolean.com).



All or select items within this series meet the requirements for these qualifications. For more information visit [americanolean.com](http://americanolean.com).