

ARCHITECTURAL & ENGINEERING SPECIFICATION

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with triple filtered by-pass, bedpan washer and Clinical sink faucet. The valve comes with a non-hold open and no leak handle. Internal seals are made of chloramine resistant materials.

PRODUCT FEATURES

- Zurn's AquaVantage® TPE diaphragm
 Triple Filtered by-pass
 Chloramine resistant
 Dual seal
- Proprietary DR resistant low lead brass alloy
- Actuator
 Non-hold open and No Leak Handle
- Control Stop
 Internal siphon-guard protection
 Vandal resistant stop cap
 Sweat solder kit
 Cast wall flange with set screw
- Vacuum Breaker
 High back pressure
 One piece hex coupling nut
- Internal seals
 Chloramine resistant
- Bedpan Washer
- Spud coupling and flange for top spud connection
- Clinical Sink Faucet : ZURN Z842M4-XL-LS1-2XT
 Polished chrome plated cast brass body Quarter-turn ceramic disc cartridges Inlets with integral stops on 8" centerline 6" centerline cast brass vacuum breaker spout 4" vandal resistant color-coded wrist blade handles



FLOW OPTIONS

	FLUSH VOLUME GPF
-FF	4.5
-STANDARD	6.5
-WS	3.5
-WS1	1.6

SUFFIX OPTIONS

- BG BioCare ADAHandle
- H Handle on Front of Flush Valve
- L 1" [25mm] Metal Push Button
- L3 3" [76mm] Metal Push Button
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

VALVE HEIGHT OPTIONS

PRODUCT NUMBER	DIMENSION A INCH [MM]
Z60842AV-BWN	34 3/8" [873]
Z60842AV-BWN2	37 3/8" [949]

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in dimensions/Overview dimensions

