

# SERLIANA™

GLAZED PORCELAIN

**MARAZZI**®

DARE TO BE BOLD™

## MOROCCAN MOSAIC 14 x 12 SHEET




**SE25** White




**SE26** Off White




**SE27** Taupe



**SE28** Dark Tan



**SE30** Blue




**SE29** Gray


## USAGE

Floors	Walls	Countertops
	W	

**SIZES**

		Thickness	Sq. Ft./ Carton	Pieces/ Carton	
	Moroccan Mosaic 14 X 12 Sheet (Mesh-Mounted)	(14-3/8" x 12-7/16") (36.49 cm x 31.57 cm)	7/16"	9.7	10

**INSTALLATION**

Grout Joint Recommendation	Shade Variation
1/8"	 Medium Variation

**APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

**PERFORMANCE CHARACTERISTICS**

	ASTM#	Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

**NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmations should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors)

Use of a White latex modified thin-set is recommended for installation.



Wall Tile



All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).