

XP-RM1.5U-6C



CommScope XPND™ 1.5Ru empty panel, accepts 6 XPND modular cassettes, providing up to 72 SC ports or 144 LC ports

- Components can be installed and removed from front or rear of panel
- Supports 12f and 24f applications while maintaining full panel density
- Cable mounting system allows for multiple trunk cables to be routed in the rear of panel

Product Classification

Regional Availability	Latin America North America Asia Australia/New Zealand
Product Type	Fiber patch panel
Product Brand	CommScope XPND™

General Specifications

Color	White
Interface, front	Unloaded
Rack Type	EIA 19 in
Rack Units	1.5
Shelf Movement	Fixed
Total Ports, quantity	0

Dimensions

Height	66.67 mm 2.625 in
Width	431.8 mm 17 in
Depth	304.8 mm 12 in

Material Specifications

Material Type	Aluminum Steel
----------------------	------------------

XP-RM1.5U-6C

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

Packaging and Weights

Packaging quantity	1
Weight, net	5.375 kg 11.85 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

