

## **Safety Data Sheet**

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 26-0472-6
 Version Number:
 4.01

 Issue Date:
 05/03/21
 Supercedes Date:
 03/08/16

#### **Product identifier**

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Reenterable Electrical Insulating Resin 2123 Kit (A & B)

## **ID** Number(s):

78-8126-6762-0, 78-8126-6763-8, 80-6112-6441-9, 80-6112-6442-7, 80-6114-7161-8, 80-6116-0939-9, 80-6116-1271-6

7000031696, 7000006197, 7100165378, 7100015525

#### Recommended use

Electrical, Two part curing system for electrical insulation

#### Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** Electrical Markets Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

25-0707-7, 25-0695-4

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



## **Safety Data Sheet**

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-0695-4
 Version Number:
 4.02

 Issue Date:
 08/30/23
 Supercedes Date:
 04/30/21

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>™</sup> Scotchcast<sup>™</sup> Reenterable Electrical Insulating Resin 2123, Part A

### **Product Identification Numbers**

80-6116-1272-4 7100175502

#### 1.2. Recommended use and restrictions on use

### Recommended use

Electrical, Part A of two part electrical resin

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Electrical Markets Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

## 2.1. Hazard classification

Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1A. Reproductive Toxicity: Category 1B.

#### 2.2. Label elements

#### Signal word

Danger

#### **Symbols**

Health Hazard |

## **Pictograms**



#### **Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

## **Precautionary Statements**

### **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

### **Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

28% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
SOYBEAN OIL	8001-22-7	60 - 75 Trade Secret *
BUTADIENE-MALEIC ANHYDRIDE COPOLYMER	25655-35-0	15 - 30 Trade Secret *
EPOXIDIZED SOYBEAN OIL	8013-07-8	1 - 10 Trade Secret *
ВНТ	128-37-0	< 1 Trade Secret *
MALEIC ANHYDRIDE	108-31-6	< 1 Trade Secret *
Toluene	108-88-3	< 0.3 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eve Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbonsDuring CombustionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with

applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

## 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
MALEIC ANHYDRIDE	108-31-6	ACGIH	TWA(inhalable fraction and vapor):0.01 mg/m3	A4: Not class. as human carcin, Dermal/Respiratory Sensitizer
MALEIC ANHYDRIDE	108-31-6	OSHA	TWA:1 mg/m3(0.25 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
ВНТ	128-37-0	ACGIH	TWA(inhalable fraction and vapor):2 mg/m3	A4: Not class. as human carcin
DUST, INERT OR NUISANCE	8001-22-7	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	8001-22-7	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	8001-22-7	ACGIH	TWA(respirable particles):3 mg/m3	
VEGETABLE OIL MIST, TOTAL DUST	8001-22-7	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

\_\_\_\_\_

STEL: Short Term Exposure Limit CEIL: Ceiling

### 8.2. Exposure controls

## 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - Neoprene Apron - Nitrile

## **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Liquid

Color Brown, Transparent Yellow

**Specific Physical Form:** Resin

OdorMild HydrocarbonOdor thresholdNo Data AvailablepHNo Data AvailableMelting pointNo Data Available

**Boiling Point** 475 °F

Flash Point >= 300 °F [Test Method:Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data Available

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

No Data Available

\*= 27 psia [@ 131 °F]

No Data Available

\*\*Provided To Provide The Provided The Provide

**Density** 0.89 g/ml

Specific Gravity 0.89 [Ref Std:WATER=1]

Solubility in WaterNegligibleSolubility- non-waterNo Data Available

Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Average particle size No Data Available **Bulk density** No Data Available **Hazardous Air Pollutants** No Data Available Molecular weight No Data Available **Volatile Organic Compounds** No Data Available

Percent volatile
Softening point
No Data Available
No Data Available
VOC Less H2O & Exempt Solvents
No Data Available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids Strong bases Reducing agents

Strong oxidizing agents

No Data Available

### 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

.....

## 11.1. Information on Toxicological effects

## Signs and Symptoms of Exposure

## Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

## **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

### **Additional Health Effects:**

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
SOYBEAN OIL	Dermal		LD50 estimated to be > 5,000 mg/kg
SOYBEAN OIL	Ingestion		LD50 estimated to be > 5,000 mg/kg
EPOXIDIZED SOYBEAN OIL	Dermal	Rabbit	LD50 > 20,000 mg/kg
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	LD50 > 5,000 mg/kg
BHT	Dermal	Rat	LD50 > 2,000 mg/kg
BHT	Ingestion	Rat	LD50 > 2,930 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation- Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
MALEIC ANHYDRIDE	Dermal	Rabbit	LD50 2,620 mg/kg
MALEIC ANHYDRIDE	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
SOYBEAN OIL	Professio nal judgeme nt	Minimal irritation

**Page** 7 **of** 13

EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
BHT	Human	Minimal irritation
	and	
	animal	
Toluene	Rabbit	Irritant
MALEIC ANHYDRIDE	Human	Corrosive
	and	
	animal	

Serious Eye Damage/Irritation

Name Name	Species	Value
SOYBEAN OIL	Professio nal judgeme nt	Mild irritant
EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
BHT	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
MALEIC ANHYDRIDE	Rabbit	Corrosive

## **Skin Sensitization**

Name	Species	Value
EPOXIDIZED SOYBEAN OIL	Guinea	Not classified
	pig	
ВНТ	Human	Not classified
Toluene	Guinea	Not classified
	pig	
MALEIC ANHYDRIDE	Multiple	Sensitizing
	animal	
	species	

**Respiratory Sensitization** 

Name	Species	Value
MALEIC ANHYDRIDE	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value		
EPOXIDIZED SOYBEAN OIL	In Vitro	Not mutagenic		
BHT	In Vitro	Not mutagenic		
BHT	In vivo	Not mutagenic		
Toluene	In Vitro	Not mutagenic		
Toluene	In vivo	Not mutagenic		
MALEIC ANHYDRIDE	In vivo	Not mutagenic		
MALEIC ANHYDRIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	Not carcinogenic
ВНТ	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Page 8 of 13

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
ВНТ	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
ВНТ	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
ВНТ	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
MALEIC ANHYDRIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesi s

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
MALEIC ANHYDRIDE	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
EPOXIDIZED SOYBEAN OIL	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	2 years
ВНТ	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
ВНТ	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
ВНТ	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
ВНТ	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation

Page 9 of

ВНТ	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
MALEIC ANHYDRIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
MALEIC ANHYDRIDE	Inhalation	endocrine system   hematopoietic system   nervous system   kidney and/or bladder   heart   liver   eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
MALEIC ANHYDRIDE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
MALEIC ANHYDRIDE	Ingestion	skin   endocrine system   immune system   eyes   respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

## **Aspiration Hazard**

**Page** 10 **of** 13

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

## **EPCRA 311/312 Hazard Classifications:**

Physical Hazards	
Not applicable	

# Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

## 15.2. State Regulations

Contact 3M for more information.

## 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

## NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

## **HMIS Hazard Classification**

Health: \*2 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

25-0695-4 **Version Number:** 4 02 **Document Group: Issue Date: Supercedes Date:** 04/30/21 08/30/23

## Reason for Reissue

Conversion to GHS format SDS.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product. some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-0707-7
 Version Number:
 4.03

 Issue Date:
 08/30/23
 Supercedes Date:
 09/10/21

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>™</sup> Scotchcast<sup>™</sup> Reenterable Electrical Insulating Resin 2123, Part B

### **Product Identification Numbers**

80-6116-1273-2 7100175498

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Electrical, Part B of two part electrical resin

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Electrical Markets Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

## 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

## Signal word

Not applicable.

### **Symbols**

Not applicable.

## **Pictograms**

Not applicable.

## 2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	65 - 80 Trade Secret *
PETROLEUM DISTILLATES		
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-	69102-90-5	15 - 30 Trade Secret *
TERMINATED		
METHYLDIDECYLAMINE	7396-58-9	1 - 10 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

## If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbonsDuring CombustionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid eye contact. For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

## **8.2.** Exposure controls

#### 8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Page 3 of 9

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Liquid Color Amber

**Specific Physical Form: Odor**Resin
Mild Odor

Odor thresholdNo Data AvailablepHNo Data AvailableMelting pointNo Data Available

**Boiling Point** >= 500 °F

Flash Point >= 450 °F [Test Method:Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor Pressure<= 1 mmHg [@ 131 °F]</th>Vapor DensityNo Data Available

**Density** 0.94 g/ml

Specific Gravity 0.94 [Ref Std:WATER=1]

Solubility In Water<= 1 % [@ 77 °F]</th>Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data Available

Autoignition temperature >= 500 °F

Decomposition temperature

No Data Available

Viscosity 500 centipoise - 750 centipoise

Average particle size No Data Available **Bulk density** No Data Available **Hazardous Air Pollutants** No Data Available Molecular weight No Data Available **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **Softening point** No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents Reducing agents

No Data Available

## 10.6. Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

## Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

## Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

## **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM	Dermal	Rabbit	LD50 > 2,000 mg/kg

Page 5 of 9

DISTILLATES			
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM	Ingestion	Rat	LD50 > 5,000 mg/kg
DISTILLATES			
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-	Dermal		LD50 estimated to be > 5,000 mg/kg
TERMINATED			
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
TERMINATED			
METHYLDIDECYLAMINE	Dermal	Rabbit	LD50 > 5,000 mg/kg
METHYLDIDECYLAMINE	Ingestion	Rat	LD50 990 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES	Rabbit	Minimal irritation
METHYLDIDECYLAMINE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES	Rabbit	Mild irritant
METHYLDIDECYLAMINE	Rabbit	Corrosive

## **Skin Sensitization**

Name	Species	Value
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES	Guinea	Not classified
	pig	

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Germ Cen Mutagementy		
Name	Route	Value
METHYLDIDECYLAMINE	In Vitro	Not mutagenic

Carcinogenicity

eur emogement,			
Name	Route	Species	Value
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES	Ingestion	Rat	Not carcinogenic
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

## **Reproductive Toxicity**

## Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED HEAVY NAPHTHENIC PETROLEUM	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
PETROLEUM DISTILLATES			classification			

## Specific Target Organ Toxicity - repeated exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Page 6 of 9

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

## **EPCRA 311/312 Hazard Classifications:**

## Physical Hazards

Not applicable

## **Health Hazards**

Hazard Not Otherwise Classified (HNOC)

### 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification

and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

## **HMIS Hazard Classification**

**Health:** 0 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 25-0707-7
 Version Number:
 4.03

 Issue Date:
 08/30/23
 Supercedes Date:
 09/10/21

## Reason for Reissue

Conversion to GHS format SDS.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available

9

directly from 3M.

3M USA SDSs are available at www.3M.com

\_\_\_\_



# **Transport Information Document**

Date: September 01, 2023 3M ID Number: 80-0002-1520-4 Product Description: 2123A RE-ENTERABLE RESIN SIZE A 2.9 OZ (82 GM) BAG Transport Protective Service: PROTECTIVE SERVICE NOT REQUIRED NMFC Sub: 00 NMFC Item: 061205 NMFC Class: 110.0 Flash Point (Closed-cup): No Flash Point UNITED STATES DEPARTMENT OF TRANSPORTATION - GROUND (U.S. DOT, 49 CFR) NOT RESTRICTED, AS PER 49 CFR 171.4, MARINE POLLUTANT EXCEPTION UNITED STATES DEPARTMENT OF TRANSPORTATION - VESSEL (U.S. DOT, 49 CFR) NOT RESTRICTED, AS PER 49 CFR 171.4, MARINE POLLUTANT EXCEPTION INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA) NOT RESTRICTED, AS PER SPECIAL PROVISION A197, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXCEPTION INTERNATIONAL MARITIME ORGANIZATION (IMO) NOT RESTRICTED, AS PER IMDG CODE 2.10.2.7, MARINE POLLUTANT EXCEPTION

The classification is authorized by the Competent Authority of the United States of America and may not meet the requirements of other competent authorities.

These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations and is valid for the original 3M package only. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING, OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.