BE806 BE-SERIES 8", 3-WAY, SHALLOW DEPTH, L,R, OR CENTER, IN-WALL LOUDSPEAKER





Freq Response Impedance Power rea. Woofer Grille PCB

Size 32 h x 12.95 w x 3.875 d (in) 812 h x 329 w x 98 d (mm) 45Hz-40kHz±3dB 8 ohms Sensitivity 96dB 2.83V/1m 50-300 watts (2) 8"(203mm) Aluminum Tweeter (4) 1"(25mm) Beryllium Black or White Cloth **Requires Framing**



2185 Park Place, Minden, NV 89423 Ph: 775.461.7500 www.jamesloudspeaker.com

(2) 8" (203mm) High Excursion Aluminum Driver (4) 1" (25mm) Beryllium Dome Tweeters in Quad-Array

The BE-series is James Loudspeaker's line of studio grade reference in-wall loudspeakers, designed and engineered for precision and sonic accuracy. There is nothing quite like the workmanship that goes into building these speakers; each unit is hand assembled, tested, and packaged by craftsman in the USA. The BE806 in-wall reference loudspeaker features high

output driver components, set into a solid aluminum baffle, coupled with James quad tweeter array, incorporating four 1" (25mm) beryllium dome tweeters in a 22.5^o offset array for wide dispersion, high power handling, and low distortion promises to deliver only the best audiophile quality sound.

Perfect for home theaters and stereo systems, these in wall speakers deliver top quality sound while saving space in any environment. The truly superior quality and design of these speakers is immediately prevalent. Equipped with a high output aluminum cone woofer and a powerful aluminum cone mid-range driver, the BE806 has an impressive 96dB sensitivity, with bass down to 45Hz, and the beryllium dome tweeters deliver the most crisp, clear high-frequencies available. The sealed cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Designed for easy installation into 2x4 stud walls, 16" on center, with some additional stud framing required.

For outdoor/marine applications, order the BE806-M.









THE APEX OF SOUND 20220107