

MASILLA METALICA

Technical Data Sheet

Creation Date 25/10/2018

Version I

A universal surface repair. The putty consists of a pre-accelerated polyester resin and environment-friendly fillers. There is no styrene in this product.

Where to use?

The complete hobby and DIY sector can benefit from this product. Holes <12mm in metal, wood and concrete can be filled with this 2 component polyester putty.

How does it work?

This two component putty is styrene free. It has an excellent adhesion to a variety of surfaces. The cured resin is easy to sand and has a good resistance to household chemicals.

What to expect?

A fast curing putty, giving excellent grip to anchor bolts, safe repair of stair steps... With the CRC Masilla Metalica, you have the possibility to make brilliant repair jobs.

Be prepared

- Read the instructions on the can attentive.
- Make sure to have a good ventilation.
- Wear protective safety goggles and nitril gloves.
- Dispose empty cans according to your local legislation.

Help for a good application

- Grind or sand the surface until there is a smooth, bare material.
- Start with coarse sanding paper going up to a grade 200.
- Degrease the surface.
- Take the requested part of putty out of the can and put it in a mixing cup.
- Add the corresponding amount of hardener to the putty and mix well until you have a uniform color of the paste.
- Apply the mixed material with a spatula on the cavities to fill.
- Spread the putty as identical in shape as possible with the surrounding surface.
- Do not return non used product back into the can.
- Respect a curing time of 30 to 40 minutes before starting to sand. Now, in sanding, go up to the desired grade according to the post treatment chosen.
- Dust off and degrease before painting.

Technical data (Aerosol)

Volume:	250ml / 500ml
Basis:	Polyester resin with mineral fillers
Colour:	ochre
Application temperature:	minimum 12°C
Drying time (dry to touch):	can be sanded after 30-40 min(@20°C , 50%RH)
Mixing ratio:	2-4 % hardener to add to the resin
Pot life:	7 – 8 minutes
Allowed primers:	CRC Pro Paint Primer



**Related products:**

- CRC Power Clean
- CRC Pro Paint Primer
- CRC Pro Paint; in the desired color

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.