HUBBELL Wiring Device-Kellems

Straight Blade Devices, Female Connector Body, Insulgrip Heavy Duty, Industrial/Commercial Grade, Straight, 20A 125V, 5-20R and White

By Hubbell Wiring Device-Kellems Catalog # HBL5369C

Straight Blade Devices, Female Connector Body, Insulgrip Heavy Duty, Industrial/Commercial Grade, Straight, 2- Pole 3-Wire Grounding, 20A 125V, 5-20R, Black and White, Single Pack.



General

Application

Catalog Number Color

Cord Range EU RoHS Indicator Environmental Conditions

Horsepower - Maximum Insulation Item Type Material Material - Mounting Hardware Number Of Poles Operating Temperature

Performance

Series Style Temperature Rating

Type UPC

Dimensions

Dimensions Display Size Height Length Weight Width Industrial/Commercial Grade HBL5369C Noir, blanc 0.250"-0.655" (6.4-16.6) Yes Indoor Dry Unless Protected By Additional Means 1 Insulated Body Insulgrip Plug Polycarbonate Cord Mounted 2-Pole Maximum continuous 75°C and minimum -40°C without Impact Electrical - Current Interrupting - Certified for current interrupting at full rated current Electrical - Dielectric Voltage -Withstands 2,000V minimum Environmental - Flammability -UL 94 HB or better Environmental - IP Suitability -IP20 Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact) Mechanical - Terminal Accommodation - #18-10 AWG. Standed copper wire only Mechanical - Terminal

Identification - Terminals identified in accordance with UL 498 and CSA

Insulgrip® Standard Max Continuous- 75 Degrees C, Minimum- -40 Without Impact Connector Body 783585174259

2.78 in x 1.41 in x 1.53 in

Standard

1.53 in

2.78 in 0.15 lb

1.41 in

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Dielectric Strength Phase Voltage Rating Voltage Rating Description

Screw Terminals 20 A 20 A Withstands 2,000V minimum Single Phase 125 VAC 125 V

20 A

Conductor Related

Conductor Range Number Of Wires Wire Size #18 AWG to #10 AWG 3-Wire #18 AWG to #10 AWG

Certifications And Compliance


Industry Standard(s)	CSA Certified to C22.2 No. 42 File 280
	NEMA® WD-6 Compliant
	UL Listed to UL498 File E1706
Nema Rating	5-20R
Standards - RoHS Compliance	СМ
Status	

Logistics

Carton Quantity	10
Pallet Quantity	4000

Product Assets

Catalogs - WDK Catalog Full 2024 Warranty - Industrial & Commercial Products



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL5369C-SPEC-EN | REV 6/2024