

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name : RED OXIDE PRIMER  
UFI : RJEY-J8PU-2000-VMTE  
Product code : BDS002097AE  
Vaporizer : Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses**

Main use category : Professional use  
Use of the substance/mixture : Paints

**1.3. Details of the supplier of the safety data sheet****Supplier**

CRC Industries Europe UK Limited  
Wylds Road  
Castlefield Industrial Estate  
TA6 4DD Bridgwater Somerset  
United Kingdom  
T +44 1278 727200, F +44 1278 425644  
[hse.uk@crcind.com](mailto:hse.uk@crcind.com), [www.crcind.com](http://www.crcind.com)

**Only Representative**

CRC Industries Europe B.V.  
Touwslagerstraat 1  
9240 Zele  
Belgium  
T +32(0)52/45.60.11, F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com), [www.crcind.com](http://www.crcind.com)

**1.4. Emergency telephone number**

Emergency number : +44 1278 727200  
Office hours: 9-17h CET

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol, Category 1 H222;H229  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336  
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412  
Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.  
Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger  
Contains : acetone; propan-2-one; propanone;n-butyl acetate;2-methoxy-1-methylethyl acetate  
Hazard statements (CLP) : H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H319 - Causes serious eye irritation.

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	: H336 - May cause drowsiness or dizziness. H412 - Harmful to aquatic life with long lasting effects. P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains 4-morpholinecarbaldehyde (4394-85-8). May produce an allergic reaction.
Extra phrases	: Without adequate ventilation formation of explosive mixtures may be possible.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	25 - <50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	10 - <12,5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
propane substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	10 - <12,5	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butane substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	5 - <10	Flam. Gas 1, H220 Press. Gas (Liq.), H280
isobutane substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	2,5 - <5	Flam. Gas 1, H220 Press. Gas (Liq.), H280

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (BE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	< 2,5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
trizinc bis(orthophosphate)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
reaction mass of ethylbenzene and xylene substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	< 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	< 2,5	Flam. Liq. 3, H226 STOT SE 3, H336
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] substance with national workplace exposure limit(s) (BE) (Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	< 1	Carc. 2, H351
4-morpholinecarbaldehyde	CAS-No.: 4394-85-8 EC-No.: 224-518-3 REACH-no: 01-2119987993-12	$\leq 0,5$	Skin Sens. 1, H317

### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	(50 $\leq$ C < 100) Eye Irrit. 2; H319

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Call a poison center or a doctor if you feel unwell.

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Other information	: Dispose of materials or solid residues at an authorized site.

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.
--------------------	---

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

<b>acetone; propan-2-one; propanone (67-64-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Acetone
IOEL TWA	1210 mg/m <sup>3</sup>
	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétone # Aceton
OEL TWA	594 mg/m <sup>3</sup>
	246 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	492 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>n-butyl acetate (123-86-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle # n-Butylacetaat
OEL TWA	238 mg/m <sup>3</sup>
	50 ppm
OEL STEL	712 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>propane (74-98-6)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>butane (106-97-8)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m <sup>3</sup>
	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>isobutane (75-28-5)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL STEL	2370 mg/m <sup>3</sup>
	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>ethanol; ethyl alcohol (64-17-5)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Alcool éthylique # Ethanol
OEL TWA	1907 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>reaction mass of ethylbenzene and xylene</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
	50 ppm

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

reaction mass of ethylbenzene and xylene	
IOEL STEL	442 mg/m <sup>3</sup> 100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
OEL TWA	221 mg/m <sup>3</sup> 50 ppm
OEL STEL	442 mg/m <sup>3</sup> 100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m <sup>3</sup> 50 ppm
IOEL STEL	550 mg/m <sup>3</sup> 100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Acétate de 2-(1-méthoxy)propyle # 2-(1-Methoxy)propylacetaat
OEL TWA	275 mg/m <sup>3</sup> 50 ppm
OEL STEL	550 mg/m <sup>3</sup> 100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Belgium - Occupational Exposure Limits	
Local name	Titane (dioxyde de) # Titaandioxide

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <math>\leq 10 \mu\text{m}</math>] (13463-67-7)</b>	
OEL TWA	10 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

### DNEL and PNEC

<b>acetone; propan-2-one; propanone (67-64-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	2420 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	10,6 mg/l
PNEC aqua (marine water)	1,06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	30,4 mg/kg dwt
PNEC sediment (marine water)	3,04 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	29,5 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>n-butyl acetate (123-86-4)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,18 mg/l
PNEC aqua (marine water)	0,018 mg/l
PNEC aqua (intermittent, freshwater)	0,36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0,981 mg/kg dwt
PNEC sediment (marine water)	0,0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35,6 mg/l
<b>ethanol; ethyl alcohol (64-17-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	1900 mg/m <sup>3</sup>

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>ethanol; ethyl alcohol (64-17-5)</b>	
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	950 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, inhalation	950 mg/m <sup>3</sup>
Long-term - systemic effects, oral	87 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	114 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	206 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,96 mg/l
PNEC aqua (marine water)	0,79 mg/l
PNEC aqua (intermittent, freshwater)	2,75 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3,6 mg/kg dwt
PNEC sediment (marine water)	2,9 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,63 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	0,72 g/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	580 mg/l
<b>trizinc bis(orthophosphate) (7779-90-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0,83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	20,6 µg/l
PNEC aqua (marine water)	6,1 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	117,8 mg/kg dwt
PNEC sediment (marine water)	56,5 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	35,6 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 µg/l

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>reaction mass of ethylbenzene and xylene</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	442 mg/m <sup>3</sup>
Acute - local effects, inhalation	442 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>
Long-term - systemic effects, oral	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65,3 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2,31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6,58 mg/l
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	550 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, oral	500 mg/kg bodyweight/day
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,635 mg/l
PNEC aqua (marine water)	0,0635 mg/l
PNEC aqua (intermittent, freshwater)	6,35 mg/l

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3,29 mg/kg dwt
PNEC sediment (marine water)	0,329 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,29 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	11,7 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	50,3 mg/m <sup>3</sup>
Long-term - local effects, inhalation	13,3 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	4,17 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	8,93 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4,17 mg/kg bodyweight/day
Long-term - local effects, inhalation	13,3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,5 mg/l
PNEC aqua (marine water)	0,05 mg/l
PNEC aqua (intermittent, freshwater)	5 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1,85 mg/kg dwt
PNEC sediment (marine water)	0,185 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,0764 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2000 mg/l

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protection equipment

#### Personal protective equipment symbol(s):



# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl-rubber protective gloves.

### Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX - P2

### Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Grey.
Appearance	: Propane/butane propelled liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: 1,2 vol %
Upper explosion limit	: 13 vol %
Flash point	: -39 °C
Auto-ignition temperature	: 365 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: 8300 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,8 g/cm <sup>3</sup> at 20 °C
Relative density	: 0,8 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### Information with regard to physical hazard classes

% of flammable ingredients : ≥ 50 %

#### Other safety characteristics

VOC content : 677,8 g/l

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute toxicity (oral)</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Acute toxicity (dermal)</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Acute toxicity (inhalation)</b>	: Not classified (Based on available data, the classification criteria are not met)

#### acetone; propan-2-one; propanone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight
LD50 dermal	> 15688 mg/kg bodyweight
LC50 Inhalation - Rat	76 mg/l/4h

#### n-butyl acetate (123-86-4)

LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	23,4 mg/l/4h

#### ethanol; ethyl alcohol (64-17-5)

LD50 oral rat	15010 mg/kg bodyweight
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat (Vapours)	> 116,9 mg/l/4h

#### trizinc bis(orthophosphate) (7779-90-0)

LD50 oral rat	> 5000 mg/kg bodyweight
---------------	-------------------------

#### reaction mass of ethylbenzene and xylene

LD50 dermal rabbit	12126 mg/kg bodyweight
--------------------	------------------------

#### 2-methoxy-1-methylethyl acetate (108-65-6)

LD50 oral rat	> 5000 mg/kg
LD50 oral	8532 mg/kg bodyweight

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 10800 mg/l
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
LD50 oral rat	> 7314 mg/kg bodyweight
LD50 dermal rabbit	> 18400 mg/kg bodyweight
LC50 Inhalation - Rat	> 5,319 mg/l/4h
<b>Skin corrosion/irritation</b>	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
<b>n-butyl acetate (123-86-4)</b>	
pH	6,2
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
pH	10
<b>Serious eye damage/irritation</b>	: Causes serious eye irritation. pH: Not applicable
<b>n-butyl acetate (123-86-4)</b>	
pH	6,2
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
pH	10
<b>Respiratory or skin sensitisation</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Germ cell mutagenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Carcinogenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Reproductive toxicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>STOT-single exposure</b>	: May cause drowsiness or dizziness.
<b>acetone; propan-2-one; propanone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>reaction mass of ethylbenzene and xylene</b>	
STOT-single exposure	May cause respiratory irritation.
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>STOT-repeated exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>n-butyl acetate (123-86-4)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
<b>ethanol; ethyl alcohol (64-17-5)</b>	
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight
<b>reaction mass of ethylbenzene and xylene</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>reaction mass of ethylbenzene and xylene</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight
<b>Aspiration hazard</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>RED OXIDE PRIMER</b>	
Vaporizer	Aerosol
<b>n-butyl acetate (123-86-4)</b>	
Viscosity, kinematic	0,83 mm <sup>2</sup> /s
<b>reaction mass of ethylbenzene and xylene</b>	
Viscosity, kinematic	0,76 mm <sup>2</sup> /s

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>acetone; propan-2-one; propanone (67-64-1)</b>	
LC50 - Fish [1]	5540 mg/l
EC50 - Other aquatic organisms [1]	12600 mg/l Daphnia magna (Water flea)
LOEC (chronic)	> 79 mg/l
NOEC (chronic)	≥ 79 mg/l
<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674,7 mg/l
LOEC (chronic)	47,6 mg/l
NOEC (chronic)	23,2 mg/l
NOEC chronic algae	200 mg/l

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>ethanol; ethyl alcohol (64-17-5)</b>	
LC50 - Fish [1]	14,2 g/l
EC50 - Other aquatic organisms [1]	5012 mg/l
ErC50 algae	275 mg/l
NOEC (chronic)	9,6 mg/l
<b>reaction mass of ethylbenzene and xylene</b>	
LC50 - Fish [1]	2600 mg/l Oncorhynchus mykiss
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 500 mg/l
EC50 - Other aquatic organisms [1]	408 mg/l
EC50 - Other aquatic organisms [2]	> 1000 mg/l
EC50 72h - Algae [1]	> 1000 mg/l
NOEC (chronic)	≥ 100 mg/l
NOEC chronic fish	47,5 mg/l
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
LC50 - Fish [1]	> 500 mg/l Leuciscus idus
EC50 - Crustacea [1]	> 500 mg/l Daphnia magna
EC50 72h - Algae [1]	23880 mg/l Desmodesmus subspicatus
EC50 72h - Algae [2]	17440 mg/l Desmodesmus subspicatus
<b>12.2. Persistence and degradability</b>	
<b>RED OXIDE PRIMER</b>	
Persistence and degradability	Not established. No data is available on the degradability of this product.
<b>12.3. Bioaccumulative potential</b>	
<b>RED OXIDE PRIMER</b>	
Partition coefficient n-octanol/water (Log Kow)	Not applicable
<b>acetone; propan-2-one; propanone (67-64-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0,24
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2,3
<b>ethanol; ethyl alcohol (64-17-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0,32
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1,2
<b>4-morpholinecarbaldehyde (4394-85-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	-1,32

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### RED OXIDE PRIMER

Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII
---------------------------	--

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

#### RED OXIDE PRIMER

Other information	No other effects known
Global warming potential (GWP)	0.93 (Fluorinated greenhouse gases - (EC) No 2024/573)






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

#### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### VOC Directive (2004/42)

VOC content : 677,8 g/l

##### Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

##### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Indication of changes

Section	Changed item	Comments
2.2	Precautionary statements (CLP)	Modified

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

# RED OXIDE PRIMER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains 4-morpholinecarbaldehyde (4394-85-8). May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.