

Features

- 2.5 gpm (9.5 lpm) maximum flow rate
- Ergonomic design is easy to use
- Changing sprays is as easy as turning the head on its axis
- Komotion® spray delivers a soothing, circular water pattern
- Kotton® spray releases a dense, luxurious downpour of water
- Koverage® spray delivers full-coverage spray for everyday showering
- Kurrent® spray offers a targeted massage to ease away aches and pains
- Adjustable angle for various user heights
- Shower hose sold separately
- With innovative Flipstream® technology, the Flipside handshower dedicates a single sprayhead surface to each of four unique sprays

Material

- KOHLER® finishes resist corrosion and tarnishing

Installation

- Bracket or slidebar required for wall-mount installation
- Deck-mount holder required for deck-mount installation

Required Products/Accessories

K-8593 72" Shower Hose

or

K-9514 60" Shower Hose

Recommended Products/Accessories

K-23723 Faucet cleaner



OBC

Codes/Standards

ASME A112.18.1/CSA B125.1



DOE - Energy Policy Act 1992

OBC

IAPMO Certification

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.



Technical Information

All product dimensions are nominal.

Drain included: No

Handshower:

Rated maximum flow: 2.5 gal/min (9.5 l/min)

Notes

For use with automatic compensating valves rated at 2.5 gal/min (9.5 l/min) or less.

Install this product according to the installation guide.

Plumbing codes require an atmospheric vacuum breaker (such as Kohler Model K-9660) be installed in-line with handshowers. Please consult with local plumbing officials.

OBC compliant when installed to the specific requirements of these regulations.