ND2T



Easy to install 2" new construction rough-in for use with RDLED2 trims. The Remodeler Trim component must be ordered with the New Construction Housing in order to make a complete fixture. Available in flush trim for a trimless look without the mess left behind from ceiling finishing work.

Weight: 1.6 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	N/A
120V	N/A
208V	N/A
240V	N/A
277V	N/A
Input Watts	0.00W

LED Info

Watts	0W
Color Temp	Sold Separately
Color Accuracy	N/A
L70 Lifespan	N/A Hours
Lumens	N/A
Efficacy	N/A

Technical Specifications

Listings

UL Listed:

Suitable for wet locations in a covered ceiling

Construction

IC Rated:

Suitable for direct contact with insulation

Housing Component:

This component must be ordered with the 2 inch downlights trim in order to make a complete fixture.
See here for Round 2" Trims
See here for Square 2" Trims

Housing:

Professional-grade, heavy-gauge steel construction with 1/2" trim

Mounting:

Housing includes nailer bars and butterfly brackets. Brackets also accommodate mounting with 1/4" to 1/2" bar stock, C channel or 1/2" conduit.

Junction Box:

Integral junction box with wiring capacity for
Min 60°C supply conductors
End of Run

Air Tight:

Housing certified Air Tight as per ASTM E283

Easy Installation:

Ceiling clamps install quickly and hold housing securely. Clamp ceilings from 1/2" to 2 1/2" thick, with course and fine adjustments.

Trim:

1/2" trim

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Buy American Act Compliance:


RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Copyright © 2020 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

ND2T

Dimensions





Features

- Butterfly bracket allows mounting with bar stock, "C" channel, 1/2" conduit or nailer bars
- Low-profile design allows for installation in ceilings with limited space
- IC rated without additional hardware required

Ordering Matrix

Family	Size	Trim
ND	2	
	2 = 2"	**T =** Trim **TL =** Trimless

Copyright © 2020 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice