

PRODUCT DESCRIPTION: The P5HD/13.50/2.7 is a rigid, durable, tapered, seamless, vacuum-formed insert designed specifically for 5-gallon plastic pails. This robust insert is molded from FDA-approved high-density polyethylene, which provides better resistance to many solvents, compared to LDPE. A contoured lip snaps over the top bead to prevent leakage between the insert and the pail wall.

Insert Specifications

MATERIAL USED

High-density polyethylene

INSERT DIMENSIONS

Diameter: 11.25" (2.7° taper) (+0.25"/-0")

Height: 13.5" (+/-0.125")

Average thickness: 15 mil (+/-10%)

WEIGHT

4 oz. (+/-10%)

SIDE-WALL DESIGN

Straight-sided (taper)

TEMPERATURE PARAMETERS

High (momentary): 180° (240°)F

Low: -20° F

Packaging Specifications

CARTON WEIGHT

30 lbs.

CARTON DIMENSIONS

Length: 24"

Width: 24"

Height: 27"

QUANTITY/CASE

100

PACKAGING STYLE

Nested, 4 stacks of 25

TYPICAL APPLICATIONS: The P5HD/13.50/2.7 is perfect for containing all liquids, powders and pastes that can be contained in high-density polyethylene, as well as resist long-term exposure to a wide range of materials. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones, and food.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG20590

DESCRIPTION:

5 gallon 15 mil HDPE Payliner