

## **ELEGANTLY MOUNT IPAD** ON ANY SURFACE.

IPORT Surface Mount is the most elegant way to mount iPad on a wall, solid surface or onto glass. Surface Mount allows access to the iPad power button, microphones and speakers. iPad is contained in a minimalist aluminum bezel and stays protected by engaging locking components in the bezel as well as on the surface.

By utilizing IPORT's PoE and a standard CAT cable, Surface Mount can be up to 300 ft. from a power source or can be hard-wired to a network employing Apple's USB to Ethernet.

Available in black, silver or white finishes, Surface Mount is the easiest way to install iPad on any surface while ensuring iPad blends into your space.



### THE SYSTEM

### SYSTEM FINISHES











AND



(OPTIONAL)

**BEZEL SPLITTER INJECTOR** 

### **BEZELS**





70797

70798

Pad mini 4   5th gen			
70722	BLACK	\$300	
70723	SILVER	\$300	
70724	WHITE	\$300	

iPad 5th gen	6th gen	
70703	BLACK	\$355
70704	SILVER	\$355
70705	WHITE	\$355

iPad 10.2-inch (	7th & 8th Gen)	iPad Air 3rd ger
70796	BLACK	\$355

\$355

\$355

**SILVER** 

WHITE



## **SPLITTER**







### **POWER**

INPUT: 36-57V 0.4A DC (PoE IEEE 802.3af) via RJ-45 AUX INPUT: 18-24V, 0.8A DC via 2-pin connector OUTPUT: 5V 2.4A DC Via USB-A

70718 BLACK \$120

## ]; [i s<sub>i</sub>

# Specs, Dims, CADs and more.

## **INJECTOR**







#### **POWER**

INPUT: 100-240V 0.8A AC OUTPUT: 56V 0.275A IEEE 802.3af via RJ-45 (PIN 3,6 +56V PIN 1,2 Return)



Specs, Dims, CADs and more.

70719 BLACK \$50

## **ACCESSORIES**



### **REDPARK SPLITTER & CABLE**

Use optionally for Power + Data to iPad in one solution.

## **POWER**

INPUT: 36-57V 0.4A DC (PoE IEEE 802.3af) via RJ-45 OUTPUT: 5V 2A DC Via USB-B

72021 BLACK \$125