


Adelaide




Adelaide Light Gray


Colors




White VTL ADWH




Cream VTL ADCR



Light Gray VTL ADLG



Dark Gray VTL ADDG




Black VTL ADBL

Sizes



24" x 48" x 9.5mm
Rectified
Matte and Polished

- White




24" x 24" x 9mm
Rectified
Matte

- White
- Cream
- Light Gray
- Dark Gray
- Black




24" x 24" x 8.5mm
Rectified
Polished

- White
- Cream
- Light Gray
- Dark Gray
- Black



12" x 24" x 9mm
Rectified
Matte

- White
- Cream
- Light Gray
- Dark Gray
- Black



12" x 24" x 8.5mm
Rectified
Polished

- White
- Cream
- Light Gray
- Dark Gray
- Black



12" x 12" x 9mm
Rectified
Matte

- White
- Cream
- Black



12" x 12" x 8.5mm
Rectified
Polished

- White
- Cream
- Black

ADELAIDE

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.62" x 47.24"	9.5 mm	Matte
24" x 48" Rectified	23.62" x 47.24"	9.5 mm	Polished
24" x 24" Rectified	23.62" x 23.62"	9 mm	Matte
24" x 24" Rectified	23.62" x 23.62"	8.5 mm	Polished
12" x 24" Rectified	11.73" x 23.62"	9 mm	Matte
12" x 24" Rectified	11.73" x 23.62"	8.5 mm	Polished
12" x 12" Rectified	11.73" x 11.73"	9 mm	Matte
12" x 12" Rectified	11.73" x 11.73"	8.5 mm	Polished

*Not all sizes/trims are available in all colors and finishes

Mosaics & Coordinating Trims*


SIZE	ACTUAL	FINISH
2" x 2" Mosaic Rectified	11.77" x 11.77"	Matte
3" x 24" Bullnose	2.91" x 23.62"	Matte
3" x 24" Bullnose	2.91" x 23.62"	Polished

Product Characteristics

TEST	MATTE	POLISHED
Breaking Strength	≥ 2200	≥ 2000
Chemical Resistance	Not Applicable	Not Applicable
DCOF	≥ 0.42	< 0.42
Deep Scratch Resistance - Unglazed	136	135
Frost Resistance	Resistant	Resistant
Mohs Hardness - EN101	9	8
Water Absorption	Not Applicable	Not Applicable
Certifications	Not Applicable	Not Applicable
Country of Origin	India	India
Shade Variation Code	v1	v1




V1 Uniform Appearance




Recommend an offset pattern ≤33%



Made in India



DCOF >0.42-Matte
≥ 0.42-Polished



Frost Resistant



Ready Ship

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	•
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Unglazed Through-Body Porcelain



Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES