



GE APPLIANCES

208/230V VARIABLE REFRIGERANT FLOW HEAT PUMP SYSTEM OUTDOOR UNIT

MWHQ096NC2CA

**8
TON**

SUBMITTAL

Job Name:

Purchaser:

Submitted To:

Construction:

Reference:

Approval:

Date:

Submitted By:

Unit:

Drawing #:



Features and Benefits

- Configurable heat pump or heat recovery.
- AVRA (Advanced Variable Refrigerant Adjustment) optimizes heating and cooling based on outdoor conditions to maximize efficiency and reduce costs.
- Diamond Shield multi-layer safety system designed to support safe and reliable operation with A2L refrigerants, incorporating multiple protection features for enhanced system safety and peace of mind.
- MRV-Link
 - Wireless communication
 - Zigbee wireless protocol
 - Simple installation
 - Easy to service
- Swing-out electrical service door and direct refrigerant cooled PCB.
- Enhanced Corrosion Protection 1500 hours of anti-corrosion black fin spray.
- Industry leading 32.3 in. low weight fan.
- AHU kit Supports third-party AHU integration with R32 MRV.
- Flexible long piping length.
- PID control: $\pm 1^\circ\text{F}$ accurate temperature control with dual pressure sensors and dual valves.
- Multiple quiet fan mode operations.
- R32 refrigerant.

Controls

Zone Controllers	N/A
Central Controllers	5", 7", 12.5"
Integration Controllers	HCM-04/HA-MA
MRV-Link Wireless Communication	Yes
Bluetooth Blackbox	Yes (App Pending)
BMS Solutions	HCM-05

Specifications

ODU	Marketing Model Name	MWHQ096NC2CA
	Nominal Capacity (Btu/h)	96,000
	Dimension: H x W x D (in)	66 1/2 x 37 x 32 1/2
	Net Weight (lbs)	601
	Sound Level (dBA)	67
	Compressor Type/Qty	DC Inverter EVI Scroll / 1
Connections	Compressor Oil Type	FW-68CA
	Maximum Number of Indoor Units	20
Operating Range	Connection Ratio (IDU/ODU Capacity)	50% – 150%
	Cooling with Snow Hood (°F)	-4 ~ 122
Electrical	Heating (°F)	-22 ~ 60
	Power Supply	208-230 / 3 / 60
Non-Ducted Performance	MCA/MOP (A)	43 / 50
	Rated Cooling Capacity @ 95°F (Btu/h)	91,000
	EER @ 95°F	11.9
	IEER	23.1
	Rated Heating Capacity @ 47°F (Btu/h)	103,000
	COP @ 47°F	3.6
	COP @ 17°F	2.4
Ducted Performance	SCHE	27.2
	Rated Cooling Capacity @ 95°F (Btu/h)	91,000
	EER @ 95°F	12.2
	IEER	21.8
	Rated Heating Capacity @ 47°F (Btu/h)	103,000
	COP @ 47°F	3.5
	COP @ 17°F	2.4
Refrigerant and Piping	SCHE	23.6
	Refrigerant Type/Charge (oz.)	R-32 / 11.46
	Liquid Pipe O.D. (in)	3/8
	Gas Pipe O.D. (in)	7/8
	High Gas Pipe O.D. (in)	7/8

For more information visit us:

GEAppliancesAirAndWater.com


©Copyright 2026 GE Appliances, a Haier Company. GE is a trademark of the General Electric Company. Manufactured under trademark license. GE Appliances has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

UNIT: Inches



No.	Name Remark	
1	Power line outlet	
2	Signal wire opening	
3	Pipe outlet for 2/3-pipe system	
4	Pipe outlet for 2/3-pipe system	
5	Drain hole	
6	Air outlet duct connection	

SUBMITTAL REVISION HISTORY

05-05-26: Submittal release.
08-06-26: Specification updates
09-03-26: Specification updates