

Quietly sophisticated with all the inherent benefits of tile, that's the story behind Victus™. Natural wood looks add warmth and comfort, whether your style leans more modern and minimal or traditional and timeless.

VICTUS™
Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  OUTDOOR  POOL 




Gray



Latte



Honey

Sizes Thickness Faces Finish Edge Grout Joint Recommendation							
	8" x 4.7" 7.87" x 4.724"						
	8mm						
	16						
	Matte						
Pressed							
3/16"							
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
Results*	IV	>500 lbf	Resistant	<0.50%	>0.55	7	V3

Product and Installation Details | ANSI A108.02
 Section 4.3.8.2 - For running bond/brick joining patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free
- Recycled Content 0% Pre- and Post-Consumer

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.