



## SLU OFFSET OR STRAIGHT



- Manufactured from electrolytic copper tubing and strip stock.
- Compact design.
- Range Taking for reduced inventories and flexibility.
- Re-Usable.
- UL 486A/B Listed and CSA Certified.
- Suitable for use in circuits rated 35KV or less; proper high voltage spacing and insulation techniques must be used.
- V-bottom collar.
- Contact Factory for listed wire combinations.
- For Copper Conductor only.
- SLU-35DB and SLU-70DB are suitable for direct burial in earth or concrete and are UL467 rated.
- SLU-35DB and SLU-70DB do not have voltage rating.
- A - UL listed combinations (2) 10 STR. or (2) 12 STR. or (2) 14 STR. or (1) 12 STR. and (1) 14 STR. or (1) 10 STR and (1) 12 STR.
- B - UL listed combinations (1) 8 STR. and (1) 4 STR. or (1) 8 STR. and (1) 6 STR. or (2) 4 STR. or (3) 8 STR. or (3) 6 STR. or (2) 8 STR and (1) 4 STR. or (2) 8 STR. and (1) 6 STR. or (1) 6 STR. and (1) 4 STR. or (2) 6 STR.
- UL File E6207

Item ID	Figure Number	Conductor Range	Screw Type	Tang Length	Length	Width	Hex Size	Standard Package Quantity	NAED/UPC Number
SLU-300	1	350 kcmil-1/0 AWG	Socket	1.5000	3.1875	1.0000	5/16	18	0783669834710