



# RADII DRINKING FOUNTAIN, REFRIGERATED & MODULAR AQUAPOINTE™ ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER MODEL M8WRFEBF-FVF

## Suggested Specification

Model M8WRFEBF-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall be recessed in design. Shall include the Aqua Pointe™ Bottle Filler with contactless activation and laminar flow. Bottle Filler alcove and cabinet finished shall be stainless steel. Shall include two vandal-resistant push buttons to activate the flow of water and a low flow one piece bubbler with flexible guard. The fountains shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Key Aqua Pointe™ bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

|                               |                                                                                                                                                                    |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Features:</b>              | • Built-in 100 micron strainer stops particles before they enter the waterway                                                                                      |
|                               | • Waterways are Lead-Free in materials & construction                                                                                                              |
|                               | • High efficiency cooling system                                                                                                                                   |
|                               | • Heavy duty galvanized steel frame                                                                                                                                |
|                               | • Contactless activation bottle filler with programmable auto shut off                                                                                             |
|                               | • Vandal-resistant push button                                                                                                                                     |
|                               | • Flexible bubbler guard                                                                                                                                           |
|                               | • Built-in filter monitor and bottle counter                                                                                                                       |
|                               | • Logos permanently formed into the alcove and stainless steel wrapper                                                                                             |
|                               | • LED lighted alcove                                                                                                                                               |
| <b>Filtration:</b>            | • Built in panel locks for easy access to chiller and filtration if applicable                                                                                     |
|                               | OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons |
| <b>Power:</b>                 | 115 Volts, 60 Hz                                                                                                                                                   |
| <b>Activation By:</b>         | Contactless Sensor on Bottle Filler and Manual Activation on Fountain                                                                                              |
| <b>Mounting Type:</b>         | In Wall                                                                                                                                                            |
| <b>Chilling Option:</b>       | 8.0 gph*                                                                                                                                                           |
| <b>Full Load Amps</b>         | 5.0 amps                                                                                                                                                           |
| <b>Rated Watts</b>            | 500                                                                                                                                                                |
| <b>Approx. Net Weight</b>     | 104 lbs                                                                                                                                                            |
| <b>Installation Location:</b> | Indoor                                                                                                                                                             |



Ships in multiple boxes.

## Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions
- Recessed mounting frame included

## Finishes

- Standard cabinet finish: Stainless steel

## Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

## Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

## Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_  
PROJECT: \_\_\_\_\_  
CONTACT: \_\_\_\_\_  
NOTES: \_\_\_\_\_  
APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice



RADII DRINKING FOUNTAIN, REFRIGERATED & MODULAR  
AQUAPOINTE™ ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER  
**MODEL M8WRFEBF-FVF**

## Accessories



### **OASIS VersaFilter III Replacement Cartridge**

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



### **One piece chrome plated brass bubbler**

OASIS Item #036700-001



[View all filters and accessories](#)



RADII DRINKING FOUNTAIN, REFRIGERATED & MODULAR  
AQUAPOINTE™ ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER  
**MODEL M8WRFEFB-FV**

