

Commercial Grade, Panel Mount and Specialty Switches, Bat Handle Switches, Double Pole Single Throw 10A 250V/10A 125V, Screw Terminals,

By Hubbell Wiring Device-Kellems
Catalog # [HBL21](#)



Switches and Lighting Controls, Commercial Grade, Panel Mount
and Specialty Switches, Bat Handle Switches, Double Pole Single
Throw 10A 250V/10A 125V, Screw Terminals,

General

Action	DPST
Catalog Number	HBL21
Color	Metallic
EU RoHS Indicator	No
Horsepower - Maximum	1.5
Item Type	Panel Mount and Bat Handle Switch
Mounting Method	Panel Mount
Number Of Poles	Double Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	Environmental - Operating Temperatures - Max Continuous- 75 °C, Minimum -40 °C Without Impact
Series	Double Pole/Single Throw
Style	Screw Terminal
Type	General Purpose
UPC	783585017099

Dimensions

Dimensions	1.97 in x 0.76 in x 1.3 in
Height	1.3 in
Length	1.97 in
Weight	0.1 lb
Width	0.76 in

Electrical Ratings

Amperage Rating	10/20 A
Connectivity	Screw Terminals
Current / Amperage Rating	10/20 A
Voltage Rating	250/125 VAC

Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalogs - WDK Catalog Full 2024](#)
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK_MX-HBL21-SPEC-EN | REV 6/2024