



Gemstone



Colors




White VTL GMWH



Cream VTL GMCR




Light Gray VTL GMLG





Greige VTL GMGG




Blush VTL GMBS





Blue VTL GMBU



Pewter VTL GMPW




Dark Grey VTL GMDG




Navy VTL GMNV



Sizes



6" x 7" x 9mm Hexagon



3" x 12" x 9mm



Green VTL GMGN

G E M S T O N E

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
6" x 7" Hexagon Glossy	5.91" x 6.81"	9.00mm	Gloss
3" x 12" Glossy	2.95" x 11.81"	9.00mm	Gloss
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
1" x 12" Quarter Round Glossy	0.35" x 11.81"	Gloss
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

	GLOSS
Breaking Strength (ASTM C648 or ISO 10545-4)	>240lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	B
DCOF	
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Not Resistant
Mohs Hardness - EN101	2
Water Absorption (ASTM C373 or ISO 10545-3)	10-18%
Certifications	N/A
Country of Origin	
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	
Interior	Commercial	•	
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glazed Ceramic



V2 Slight Variation



Frost Resistant



Water Absorption: 10-18%



Must be Sealed



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES