

# SONANCE

## VISUAL EXPERIENCE DATA SHEET

VX60R | VX62R | VX64R | VX66R

### TECHNICAL SPECIFICATIONS

SKU	VX60R 96088 - Pair	VX62R 96012 - Pair	VX64R 96013 - Pair	VX66R 96014 - Pair
Tweeter	1" (25mm) cloth dome, Ferrofluid-cooled, acoustic back chamber	1" (25mm) cloth dome, Ferrofluid-cooled, acoustic back chamber	1" (25mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber	1" (25mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber
Woofer	6.5" (165mm) textured polypropylene cone, rubber surround	6.5" (165mm) textured polypropylene cone, rubber surround, pivoting	6.5" (165mm) textured polypropylene cone, rubber surround, pivoting	6.5" (165mm) Kevlar/Nomex cone, rubber surround, pivoting
Dispersion Technology	Sinusoidal textured waveguide	Sinusoidal textured waveguide	Sinusoidal textured waveguide	Sinusoidal textured waveguide
Speaker Pivot	No Pivot	Coincident woofer and tweeter, +/-13° pivot	Coincident woofer and tweeter, +/-13° pivot	Coincident woofer and tweeter, +/-13° pivot
Frequency Response	48Hz - 20kHz +/-3dB	45Hz - 20kHz +/-3dB	45Hz - 20kHz +/-3dB	43Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum	8 ohms nominal; 6 ohms minimum	8 ohms nominal; 6 ohms minimum	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 100 watts maximum	5 watts minimum; 125 watts maximum	5 watts minimum; 125 watts maximum	5 watts minimum; 140 watts maximum
Sensitivity (2.83V/1m)	89dB SPL	89dB SPL	89dB SPL	90dB SPL
Mounting Technology	1-stage, 4 x RotoLock® Clamps	Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps	Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps	Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps

### SHARED DIMENSIONS

Round Micro Trim Grille (Dia): 9.62" (244.4mm)

Round Trimless Grille (Dia): 9.28" (235.6mm)

Square Micro Trim Grill (WxH): 9.62" x 9.62" (244.4mm x 244.4mm)

Square Trimless Grille (WxH): 9.28" x 9.28" (235.6mm x 235.6mm)


Speaker Mounting Depth (D): 4.92" (125mm)

Mounting Depth + Retrofit Encl.: 5.75" (146.1mm)


Cut-Out Dims (Dia): 8.25" (210mm)

Shipping Weight: 9 lbs. (4.1kg)


### DIMENSIONAL DRAWINGS



Cut-Out Diameter  
Front View



Mounting Depth (Open Back)  
Side View



Mounting Depth + Retrofit Enclosure  
Side View

### VX 6" ROUND ACCESSORIES

VX6R-GRILLE-T	
6" Micro Trim Round Grille / Pair	93575
VX6R-GRILLE-NT	
6" Trimless Round Grille / Pair	93576
VX6SQ-T	
6" Micro Trim Square Adapter / Pair	96030
VX6SQ-T-5PR	
6" Micro Trim Square Adapter / 5xPair	96033
VX6SQ-NT	
6" Trimless Square Adapter / Pair	93586
VX6SQ-NT-5PR	
6" Trimless Square Adapter / 5xPair	93589
VX6-ENCL-R	
6" Round Enclosure / Pair	96343
FLEXBRK-6-R	
6" Round Flex Bracket / 5x Pair	92337

#### LIMITED LIFETIME WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. ©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at [www.sonance.com](http://www.sonance.com). 991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777 • Fax: (949) 361-5151 • Technical Support: (949) 492-7777 12.11.2024