

Technical data sheet

Connector

Part no.: 50112155

S-M12A-ET

Contents

- Technical data
- Electrical connection



Figure can vary



Technical data

Basic data

Suitable for interface	Ethernet
------------------------	----------

Electrical data

Performance data

Overvoltage category	II
Rated operating current	4,000 mA
Rating voltage (DIN EN 60664-1)	250 V
Rated impulse voltage (DIN EN 60664-1)	2,500 V

Connection

Number of connections	1 Piece(s)
-----------------------	------------

Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
Material	Metal
Handle body material	Metal
No. of pins	4 -pin
Encoding	D-coded
Design	Axial
Lock	Screw fitting

Cable properties

Connection cross sections	1 x 0.75 mm ²
AWG	18
Shielded	Yes

Mechanical data

Housing material	Metal, Diecast zinc, chemically nickel-plated
Max. cable hole	6 ... 8 mm

Environmental data

Ambient temperature, operation	-40 ... 85 °C
Degree of contamination	3, EN 60947-1

Certifications

Degree of protection	IP 67
----------------------	-------

Classification

Customs tariff number	85369010
eCl@ss 8.0	27069190
eCl@ss 9.0	27069190
ETIM 5.0	EC001578
ETIM 6.0	EC001578

Electrical connection

Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
Material	Metal
Handle body material	Metal
No. of pins	4 -pin
Encoding	D-coded
Design	Axial
Lock	Screw fitting