

CyberPower

GX150C2-FC GAMING UPS SYSTEM

Protects high end electronics from power interruptions and power surges.

The CyberPower GX150C2-FC UPS is engineered for serious PC gamers who run high-end gear and can't afford power-related setbacks. This UPS delivers sine wave battery backup and advanced surge protection—perfect for protecting your performance-grade gaming PC, monitor, and accessories from blackouts, brownouts, and dangerous voltage spikes.

When the power drops, the GX150C2-FC gives you the time to keep gaming through short interruptions or shut down safely during extended outages—so your progress stays intact and your hardware stays safe. It also guards your networking gear, home theater setup, and other sensitive tech from power spikes and electrical surges.

The design fits right into your gaming rig, featuring a customizable RGB light halo with multiple color modes to match your setup's vibe. An intuitive, color LCD control panel gives you real-time info on system status, battery life, and power conditions—all at a glance.

Need fast charging? The GX150C2-FC comes equipped with dual USB-C ports (30W shared output) so you can charge your headset, phone, or wireless controllers even during an outage.

Backed by a \$500,000 Connected Equipment Guarantee and a three-year warranty, the GX150C2 gives you the confidence to push your hardware to the limit—without worrying about what's happening to your power.

TYPICAL APPLICATIONS

- Gaming Systems
- Laptop Computers
- Powering small electronics
- Home Networking
- Routers & Modems
- Personal Electronics

FEATURES

- Capacity: 1500VA / 1000W
- Topology: Line Interactive
- Waveform: Sine Wave
- Output: 120 VAC +/- 5%
- Runtime (half/full): 9.2 minutes / 2.3 minutes
- Plug type: NEMA 5-15P
- Cord Length: 5 ft.
- Outlets: 13 (6 surge only, 7 surge + battery backup)
- Outlet types: NEMA 5-15R
- USB-C charge ports: 2 (30W total)
- Surge Protection: 1445J
- ENERGY STAR® certified: Yes
- Warranty: Three-Year
- Connected Equipment Guarantee: \$500,000



GX150C2-FC

GAMING UPS SYSTEM

SPECIFICATIONS

GENERAL	
Energy Saving	GreenPower UPS™ High-Efficiency
ENERGY STAR® certified	Yes
UPS Topology	Line Interactive
INPUT	
Circuit Breaker	15 A
Cord Length	5 ft (1.5 m)
Input Frequency Range	57 Hz - 63 Hz
Input Plug Type	NEMA 5-15P
Nominal Input Voltage	81 - 144 VAC
Plug Style	Right Angle - 45° Offset
OUTPUT	
On Battery Frequency	60 Hz +/- 1%
On Battery Voltage	120 VAC +/- 5%
On Battery Waveform	Sine Wave
Outlet Type	13 x NEMA 5-15R
Outlets - Battery & Surge Protected	7
Outlets - Surge-Only Protected	6
Outlets - Widely-Spaced	2
Outlets - Total	13
Output Power Factor	0.67
Overload Protection	Internal Circuitry Limiting Circuit Breaker Protected
Typical Transfer Time	8 ms
USB Charge Port	Yes
USB Charge Port Amperage	2.5 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	2 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	30 Watts
VA	1500 VA
Watts	1000 W



BATTERY	
Battery Quantity	2
Battery Size	12 V / 9 Ah
Battery Type	Sealed Lead-Acid Battery
Replacement Battery Cartridge	1 x RB1290X2
Runtime at Full Load	2.3 min
Runtime at Half Load	9.2 min
Typical Recharge Time	8 hours
User-Replaceable Battery	Yes
SURGE PROTECTION & FILTERING	
EMI/RFI Filtration	Yes
Surge Suppression	1445 J
MANAGEMENT & COMMUNICATIONS	
Audible Alarms	Battery Mode Low Battery Overload Fault
HID Compliant USB Port	Yes
LED Indicators	Power On / Wiring Fault
Management Cable	USB Cable
PHYSICAL	
Color	Black
Form Factor	Mini-Tower
Material of Construction	Plastic

GX150C2-FC

GAMING UPS SYSTEM

SPECIFICATIONS

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.01 x 27.99 x 35.0 cm
Physical Dimensions - Width/Height/Depth (mm)	100 x 280 x 350 mm
Physical Dimensions - Width/Height/Depth (in.)	3.94 x 11.02 x 13.78 in.
Weight (kg)	11.03 kg
Weight (lb)	24.32 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	21.27 x 35.56 x 18.1 cm
Shipping Dimensions - Width/Height/Depth (mm)	212.73 x 355.6 x 180.98 mm
Shipping Dimensions - Width/Height/Depth (in)	8.375 x 14 x 7.125 in.
Weight (kg)	12.25 kg
Weight (lb)	27 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 104 °F (0 - 40 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Relative Humidity	0 - 95% (non-condensing)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1778 FCC CSA C22.2 No 107.3 ICES-003 Class B DOE
WARRANTY	
CEG Amount	\$500,000
Connected Equipment Guarantee	Lifetime
Extended Warranty Option	WEXT5YR-U2A
Product Warranty	3-Year Limited Warranty