

EASY-WRAP™

Rubber Splicing, Harness Wrap, & Duct Tape

EWRT, EWWH, EWDT SERIES



EASY-WRAP™ RUBBER SPLICING

- High quality unvulcanized rubber that will bond quickly to itself to form a solid mass of watertight protection.
- Self-fusing with liner.
- Can be used as primary insulation for electrical wires and cable splices up to 600 volts.
- Conforms to irregular shapes and is flexible to withstand expansion and contraction.
- Highly resistant to salt water, steam, oils, detergents and other chemicals.

TEMPERATURE RATING:

Dielectric strength 490 Volts per mil.

Meets HH-I-553C Grade B and ASTM D-119; UL 510 listing #2C58.

CAT. NO.	COLOR	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWRT 3022-.75	Black	22	0.750	0.030	1
EWRT 3022-1.5	Black	22	1.500	0.030	1
EWRT 3022-2	Black	22	2.000	0.030	1

EASY-WRAP™ WIRE HARNESS WRAP

- A 5 mil PVC film, coated with a rubber adhesive for high elongation and exceptional adherence.
- Excellent conformability to the wiring harness. Matte finish.



CAT. NO.	COLOR	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWWH 5060	Black	60	0.750	0.005	1

DUCT TAPE

- Superior cloth duct tapes, designed to meet all industry demands and applications.
- Uniform MD/CD tear properties.



CAT. NO.	COLOR	TENSILE (IN/LBS.)	LENGTH (YD.)	WIDTH (IN.)	THICKNESS (mm.)	STD. CTN. QTY.
EWDT-8	Silver	18	55	2.000	18	1