

Specifications

Model	G-AMP240/2.2			
Description	Class-D Two Channel Power Amplifier, 240W per channel			
Speaker Output	100V	8Ω	4Ω	2Ω
Rated Power Output (per channel)	240W	240W	240W	240W
Frequency Response	Full Range(FR) 20Hz-20KHz (+1/-2dB) HP ON 80Hz-20KHz (+1/-3dB) LP ON 20-(50Hz-250Hz) (+1/-3dB)			
Input	0.775V, 0 dBu, balanced phoenix connector by two channels			
Input Impedence	10KΩ			
THD	<0. 1% (1KHz/-3dBv, 100W)			
S/N Ratio	>80dB			
Crosstalk	>60dB, 1KHz, Max output			
Power Consumption	480W			
Power Requirement	100-120V/60Hz, 220-240V/50Hz			
Dimension (H x W x D)	89mm x 430mm x 335mm(3.5" x 16.93" x 13.19")			
Weight	6.3kg (14lb)			

Model	G-AMP500/2.2			
Description	Class-D Two Channel Power Amplifier, 500W per channel			
Speaker Output	100V	8Ω	4Ω	2Ω
Rated Power Output (per channel)	500W	500W	500W	500W
Frequency Response	Full Range(FR) 20Hz-20KHz (+1/-2dB) HP ON 80Hz-20KHz (+1/-3dB) LP ON 20-(50Hz-250Hz) (+1/-3dB)			
Input	0.775V, 0 dBu, balanced phoenix connector by two channels			
Input Impedence	10KΩ			
THD	<0. 1% (1KHz/-3dBv, 100W)			
S/N Ratio	>80dB			
Crosstalk	>60dB, 1KHz, Max output			
Power Consumption	1000W			
Power Requirement	100-120V/60Hz, 220-240V/50Hz			
Dimension (H x W x D)	89mm x 430mm x 335mm(3.5" x 16.93" x 13.19")			
Weight	6.3kg (14lb)			

