



Yale Pro[®] 2

Mortise Lock



YMM614
Keypad Push Button



YMM624
Keypad Touchscreen



YMM634
Key-free Push Button



YMM644
Key-free Touchscreen



The Yale Pro[®] 2 Mortise Lock is the smart keypad upgrade for traditional mortise locks, delivering keyless access for high-traffic entryways in apartments and multi-family buildings, like common shared spaces. While residents and guests enjoy seamless keyless entry, property owners gain peace of mind with a lock built for durability and enhanced high security. For property managers, the Pro 2 integrates effortlessly with smart property systems like Wi-Fi, Z-Wave Plus, and Zigbee, creating a streamlined, connected access solution across the property.



Single Action Egress

Meeting all code requirements, multi-family apartment doors can be unlocked in one motion.



Built-in Security

Depend on a tamper-proof, pick-resistant lock with an alarm if forcibly removed.



Ultimate Control

Create and manage up to 500 unique codes scheduled for residents, staff, and maintenance - temporary or permanent.



Design Variety

Choose from a push button or touchscreen design in a variety of finish options. Expect wear-resistant and long-term durability.

Flexible Connectivity

Connect through Bluetooth, Wi-Fi, Z-Wave Plus, Zigbee, and manage with partner apps to expand your smart building solutions.





Technical Specifications

Yale Pro[®] 2 Mortise Lock

In the Box

- Yale Pro[®] 2 Mortise Lock
- Smart Module Included*
- Installation Guide
- Screws
- Door Template
- 6 AA Batteries
- 2 Keys

*Included for Wi-Fi, Z-Wave Plus, and Zigbee models

Specifications

Deadbolt Specifications

Fits standard residential door

Power Requirements

6 AA alkaline batteries (included) with optional hardwire input for 9V DC external power; 9V battery power backup on keypad.

Door Thickness

1-3/4", 2", 2-1/4" Door thickness standard;

Strike

124mm x 32mm x 2.5mm with lip length standard

Face Bore

2-3/4" x 1-1/8"

Edge Bore

2 1/8"

Latch

1"

Backset

3/4" Throw Latch, 1" Deadbolt (optional)
2-3/4" (70MM) standard backset

Cylinder

Housing for 6-pin and 7-pin SFIC, no cylinder core provided
5-pin available

Handing

Field Reversible

Warranty & Certifications

ANSI/BHMA

ANSI/BHMA A156.13 Grade 1

UL/cUL

Functions are UL - cUL Fire Listed for use on fire doors having a rating up to and including 3-hours

Warranty

2-year electrical warranty;
3-year mechanical and finish warranty

Windstorm Certification

A250.13 Windstorm

Environmental

Operating temperature

-13F (-25C) to 151 F (66C)

Humidity

<85% non-condensation

Storage Temperature

-22F (-30C) to 176F (80C)

IP rating

IPx5

Base Models



YMM614
Keyed Push Button



YMM624
Keyed Touchscreen



YMM634
Key-free Push Button



YMM644
Key-free Touchscreen

Available Finishes



619
Satin Nickel



BSP
Black Suede



OBP
Oil Rubbed Bronze

Levers

AU
Augusta



CR
Carmel



PB
Pacific Beach



Contact your local Master Lock LLC
Door Security Solutions Team



24/7 1-855-213-5841

Yale Home ShopYaleHome.com



Scan to learn more
about these products

Yale[®], Yale Pro[®] and DoorSense[®] are registered trademarks of Master Lock Company LLC and its affiliates. Other product's brand names may be trademarks or registered trademarks of their respective owners and are mentioned for reference purposes only. ©Copyright All rights reserved. Reproduction in whole or in part without the express written permission of Master Lock Company LLC or its affiliates is prohibited. 2025.