Specifications

Sizes (Shown in RLX02 Nutmeg)

6 x 36



2 x 2 Square Mosaic UP Finish (Mounted on a 12 x 12 sheet.)

Sizes & Finishes

| 01203 0 1 111131103 | | | |
|------------------------|-------------|-------------------------|--------|
| Field Tile - Rectified | | Available in all colors | |
| Nominal (in) | Actual (mm) | Thickness (mm) | Finish |
| 6 x 36 | 147 x 897 | 9.3 | UP |

Crossville recommends a grout joint of 3mm.

Actual measurements stated in inches indicate tile is calibrated (non-rectifie

Actual measurements stated in mm indicate tile is rectified.

| Nominal (in)Nominal Size (in)Sheet Size (mm)Thickness (mm)Finish2 x 2 Square Mosaic*12 x 12298 x 2989.3UP | Mosaics | | | Available in all colors | |
|---|----------------------|-------------------|-----------------|-------------------------|--------|
| 2 x 2 Square Mosaic* 12 x 12 298 x 298 9.3 UP | Nominal (in) | Nominal Size (in) | Sheet Size (mm) | Thickness (mm) | Finish |
| | 2 x 2 Square Mosaic* | 12 x 12 | 298 x 298 | 9.3 | UP |

*Mounted on 12 x 12 sheet with a 3mm grout joint

Coordinating Trim

| Nominal (in) | Actual (mm) | Thickness (mm) | Finish |
|-----------------|-------------|----------------|--------|
| 6 x 18 Bullnose | 146 x 447 | 9.3 | UP |
| | 110 / 11/ | 5.0 | 01 |

6 x 18 Bullnose

| Product Performance | | |
|---------------------|------------|------------|
| Breaking Strength | >500 lbf | ASTM C648 |
| Bond Strength | >200 psi | ASTM C482 |
| Chemical Resistance | Unaffected | ASTM C650 |
| Frost Resistance | Resistant | ASTM C1026 |
| Water Absorption | <0.30% | ASTM C373 |
| Scratch Hardness | 7 | Mohs Scale |

Wet Dynamic Coefficient of Friction Range

Relax has a shade variation of V2.



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Relax

Crossville, Inc.

PO Box 1168 Crossville, TN 38557
 Phone
 931.484.2110

 Fax
 931.456.2956

 E-Mail
 Crossc@CrossvilleInc.com

 Web
 CrossvilleInc.com

Recommended Use

Relax is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Relax is not recommended for exterior horizontal surfaces or exterior paving. **If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%.** See CrossvilleInc.com for detailed installation instructions.

Wet Area Use for Relax Mosaics

The Relax 2 x 2 mosaics made in an unpolished finish. The AcuTestsm wet Dynamic COF of Relax is \geq 0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Relax to other tile products in wet area environments, such as residential/ commercial bathrooms, showers, and interior pool decks.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Photo right: Floor: **RLX04** ► Caviar 6 x 36 UP

On the cover: **RLX02** ► Nutmeg 6 x 36 UP

Trade Organizations



СТДА

Care and Maintenance

Regular cleaning is the best way to keep Relax tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. Please request a sample before ordering. For complete details check our website at CrossvilleInc.com.

HYDROTECT

by 🔶 CROSSVILLE,











LIT-RLX-19

RelaxPorcelain Stone[®]



Relax Porcelain Stone®

Relax into Crossville

Selecting tile should never cause worry. That's why we created Relax. Subtle, calming woodgrain in certified porcelain tile brings your project tranquil sophistication. Four natural, on-trend tones are available in a rectified 6x36 plank and accompanied by a bullnose and mosaic to complete your design scheme. Achieve peace of mind with your project, knowing Relax brings you the quality and availability you expect from Crossville.

- Beautifully durable alternative to wood
- 6x36 planks are rectified with a minimum 3mm grout joint
- Coordinating trim and mosaic



RLX03 Woolen 6 x 36 UP and 2 x 2 Mosaic

Color Palette

Available Colors

C

(



RLX01 ► Chiffon UP



RLX02 ► Nutmeg UP



RLX03 ► Woolen UP




RLX04 ► Caviar UP

Mosaics



RLX01.10202MOS Chiffon 2 x 2 Mosaic UP



RLX02.10202MOS Nutmeg 2 x 2 Mosaic UP



RLX03.10202MOS Woolen 2 x 2 Mosaic UP



RLX04.10202MOS Caviar 2 x 2 Mosaic UP



