



SPECIFICATION SHEET

9100-2120D



8.5 cal/cm² DUAL CERTIFIED, VENTED BACK COVERALL

- HRC2, ATPV 8.5 cal/cm²
- NFPA 2112-2012
- UL Certified
- Aramid high tenacity FR thread, FR rib knit cuffs
- No metal pieces on the garment
- Bar-tacked at all stress points
- Protective stand-up collar with hook & loop closure
- Storm guard with hook & loop closure
- Comfort vented back for breathability
- Action back for mobility, side elasticized waist
- Hook & loop on bottom
- 2 waist patch pockets with side access

STANDARDS MET

- NFPA 1975-2009, NFPA 2112-2012
- NFPA 70E 2012, ASTM F 1506-2010a
- CAN/CGSB 155.20-2000, CAN/CGSB 155.22-97
- OSHA 29 CFR 1910.269
- EN ISO 11611:2008, EN ISO 14116:2008
- UL Model # STC24

APPLICATIONS

- Electrical & Utilities
- Petrochemical, Gas & Oil
- Mining
- Welding
- Emergency Services

CARE INSTRUCTIONS

Machine wash warm, 165° F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

TECHNICAL DATA

MATERIAL	FR twill weave. 90% Cotton/10% Nylon
CONSTRUCTION	Main: 7oz FR twill weave. 90% Cotton/10% Nylon. Acc: Yellow FR mesh inside vented back.
COLOR	■ Royal Blue (9100-2120D)
SIZES	S - 5X
PACKAGING	1/Polybag, 18/Case
CASE	22" x 16" x 16" / 56cm x 41cm x 41cm
CASE WEIGHT	53 lbs / 24 kg
COO	China
HARM CODE	6211.32.0010


BARCODES

ITEM	BAG	BOX	CASE
■ 9100-2120D/S	616314151231	---	02616314151239
■ 9100-2120D/M	616314151248	---	02616314151246
■ 9100-2120D/L	616314151255	---	02616314151253
■ 9100-2120D/XL	616314151262	---	02616314151260
■ 9100-2120D/2X	616314151279	---	02616314151277
■ 9100-2120D/3X	616314151286	---	02616314151284
■ 9100-2120D/4X	616314151293	---	02616314151291
■ 9100-2120D/5X	616314151309	---	02616314151307



DIMENSIONS (in)

	S	M	L	XL	2X	3X	4X	5X
A	36-38	40-42	44-46	48-50	52-54	56-58	60-62	64-66
B	32-34	36-38	40-42	44-46	48-50	52-54	56-58	60-62
C	34.5	35.5	36.5	38	39.5	41	42.5	44
D	32	32	32	32	32	32	32	32



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.