



DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31535

DESCRIPTION:

48-400 Metal Screw Cap, PALF Liner

PRODUCT DATA SHEET

Pulp and Aluminum Foil (PAF)

35 Pulp

LINER DESCRIPTION

Description: A pulp backed primary liner with a barrier facing consisting of paper backed aluminum foil. This liner provides reseal and very good barrier to moisture and oxygen.

FDA Status: Complies with 21 CFR177.1210, 176.180, and 176.179

PHYSICAL AND CHEMICAL PROPERTIES

- Color** Matte Manila (non-product side);
Gloss metallic (product side)
- Thickness, mils**
 - Aluminum Foil 1.5
 - Paper 2.5
 - Pulp Board 35.0

Thickness tolerance +/- 10%
Minimum width 1.0 in
Width Tolerance +/- 0.0625

- Oxygen Transmission** Essentially Zero
- Water Vapor Transmission** Essentially Zero

Please note that construction does not reflect adhesive or resin bonding layers if present.

LINER RECOMMENDED

STORAGE CONDITIONS

The material should be stored in well-ventilated area (temp. 60° - 80°F; RH – 40% - 60%). Avoid storing over extended periods. Avoid contamination.

PAF should not be used with any aqueous, acidic, alkaline, or corrosive products.

DISTRIBUTED BY:



REF NO.:

DWG31535

DISCLAIMER
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

48-400 Metal Screw Cap, PALF Liner