Relax

Porcelain Stone®

Available Colors



RLX01 ▶ Chiffon



RLX02 ▶ Nutmeg



RLX03 ▶ Woolen



RLX04 ▶ Caviar

Features and Benefits

- Relax into Crossville's softest wood-look porcelain and enjoy enduring comfort in any space
- Competitively priced for exceptional value, Relax eases the tension between beauty and budget
- Relax offers 4 trend-forward colors featuring a subtle, sophisticated wood grain
- Understated and versatile, Relax's 6 x 36 planks deliver maximum installation flexibility
- Coordinating bullnose and 2x2 mosaic allow for fully finished looks



Relax

Porcelain Stone®

Sizes (Shown in RLX02 Nutmeg)





Get Planked!

fulfillment.

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick

See website for more details and sizes.

2 x 2 Square Mosaic UP Finish (Mounted on a 12 x 12 sheet.)

Sizes & Finishes

4	Field Tile - Rectified		Available in all colors	
	Nominal (in)	Actual (mm)	Thickness (mm)	Finish
	6 x 36	147 x 897	9.3	UP

UP

9.3

Actual measurements stated in mm indicate tile is rectified.

Mosaics		4	Available in all colors
Nominal (in)	Nominal Size (in)	Shee	et Size (mm) Thickness (mm) Finish

12 x 12

2 x 2 Square Mosaic* *Mounted on 12 x 12 sheet

Coordinating Trim	4		
Nominal (in)	Actual (mm)	Thickness (mm)	Finish
6 x 18 Bullnose	146 x 447	9.3	UP

298 x 298



6 x 18 Bullnose

Product Performance


Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.30%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UP 0.4	.42 - 0.52	AcuTestsm
--------	------------	-----------

Shade & Texture Index

Relax has a shade variation of V2.



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



V2 Slight Variation

Relax

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 **Phone** 931.484.2110 **Fax** 931.456.2956

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Relax is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Relax is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%. See CrossvilleInc. com for detailed installation instructions.

Wet Area Use Mosaics

The Relax 2 x 2 mosaic is made in an unpolished finish (UP). The AcuTestsm wet Dynamic COF of Relax is \geq 0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Relax to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Relax tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest. most accurate information.

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defence against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. Please request a sample before ordering. For complete details check our website at CrossvilleInc.com.

WHYDROTECT

by **CROSSVILLE**,

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Crossville® Sample Express

Complimentary Samples are available at CrossvilleInc.com/products/relax/

Samples may also be ordered through customer service by email or phone.

Sample Fulfillment & Help Line Samples@CrossvilleInc.com

1800 221.9093 Loose Tile Samples

for Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series

Max. of 4 large field tile per order

Replacement Chips for PSS Rack Max. of 5, 2 x 2 chips per color

Sandard Shipping

UPS Ground

Trade Organizations

















