



CRC Belt Dressing

I. General Description

CRC Belt Dressing is a synthetic polymer based formulation. It extends the life of belts and pulley bearings by improving traction and allowing runs under reduced belt tension.

Slippage prevention for all types of belts.

2.Characteristics

- Prevents slippage on flat, round and V-belts.
- Adheres strongly to any belt material.
- Gives extra pulling power, enhances transmission efficiency.
- Reduces squeaking noise caused by belt slipping.
- Forms a tacky, non-drying, water-resistant, chemically stable film.
- Compatible with all commonly used types of belt materials (rubber, leather, fabrics, ...).
- Aerosols are equipped with a 360° (upside-down) spray valve and provided with an extension tube for added convenience.

3.Applications

Eliminate slippage in flat, round or V-belts made out of rubber, leather, fabrics, plastic... used in:

- Compressors
- Pumps
- Generators
- Fans
- Motors
- Automobiles
- Lift trucks
- Warehousing
- Conveyor belts
- Sloping belts
- Transport belts



CRC Belt Dressing

4. Instructions

- Turn off equipment and stop belts before applying.
- Do not mix with other lubricants.
- Apply to a clean and dry surface.
- Spray a light, even coating on the pulling sides of the belt.
- Re-apply occasionally to ensure continued high performance.
- Allow the solvent to evaporate for a couple of minutes before starting the equipment

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

- | | | |
|-------------------------|---|---------------------------------|
| • Appearance | : | clear liquid |
| • Density | : | 0.79 g/cm ³ (@ 20°C) |
| • Flash Point | : | < 0 °C (Closed Cup) |
| • Operating temperature | : | Max 200°C |

6. PACKAGING

Aerosol: 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Date: 09/03/2023