

20 ft. Smart Color Chasing LED Strip Light



- Ultrathin flexible tape can light up any part of the house
- Set color, brightness, movement and effects, scenes and more with app control or Alexa / Google
- Choose from millions of colors or tunable shades of white

Product Specifications

Item Number: **TAPE20/CHASE/UK/EU**

Lighting technology used	LED
Non-directional or directional	Non-Directional
Light source cap-type (or other electric interface)	N/A
Correction factor C depending on light source characteristics-Main or non-mains	Non-Main
Connected light source (CLS):	N/A
Useful luminous flux(Lm)*	190
Correlated colour temperature (K) *	2700
Chromaticity coordinate (x):	0.463
Chromaticity coordinate (y):	0.42
The beam angel or range of beam angles(0)*	N/A
Beam angle correspondence : Sphere or wide cone or narrow cone	Sphere
Electrical interface details*	
The L70B50 life time expressed in hours	15,000
The on-mode power (Pon) expressed in W	3
Lamp Dimensions(mm)	1000*10*2.7
The standby power (Psb) expressed in W	N/A
The networked standby power (Pnet) for CLS expressed in W	N/A
The Colour rendering index 80	80
Survival factor (Max value =1)	1
Lumen maintenance factor (Max value =1)	93.1%
Displacement factor (Max value =1)	0.5
Colour consistency in McAdam ellipses (Max value =9)	6
Flicker metric (Max value =9.9)	1.0
Stroboscopic effect metric (Max value =9.9)	0.4
Spectral power distribution in the range 250 nm to 800 nm, at full-load (File to be uploaded)	
If the light source is designed for optimum use in nonstandard conditions (such as ambient temperature Ta \neq 25 0C or specific thermal management is necessary)	N/A
A warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods	Wireless Dimming
Mercury content x,x mg (if applition) 0,0	N/A
Energy consumption in on-mode (KWh/1000h):	3
Energy Efficacy Class	G